

Creating diagrams for chess problems

Version v1.22

Thomas Brand Stefan Höning
Bornheim Neuss

2024/06/13

Abstract

It have been more than ten years now, since we last published a documented version of the `diagram.sty`, which is mainly intended to be used for typesetting chess problems. Since 1994 I (Stefan Höning) made a couple of enhancements to the sourcecode of the style, without publishing and putting this into the documentation. We also needed to upgrade to L^AT_EX 2_&. The major change is the documentation language, which is english now.

The style itself tries to collect very detailed information about a chess problem by providing a lot of commands, which you may use to specify the necessary information. There are different reasons for this. One idea was to enable people to read L^AT_EX-diagrams into databases with information as detailed as possible. Otherwise it should be easy to change the layout of a diagram by applying a changed style - not by changing the source.


Contents

1	Creating diagrams	3
1.1	An introductory example	3
1.2	Elements of a diagram	4
1.2.1	Collecting the problem information	4
1.2.2	Modifying the layout of the diagram (and the solution) .	7
1.2.3	Other commands	8
1.3	Special boards	8
1.3.1	Changing the boardsize	8
1.3.2	Stereo- and Space-Chess-Diagrams	9
1.3.3	Cylindric boards / suppressing frames	11
1.4	Change the coloring of the fields	11
1.4.1	figurine Notation	12
1.4.2	Changes within the board	12
1.5	Misc	13
1.5.1	Chess pieces within normal text	13
1.5.2	Other often used symbols	14
1.5.3	Internationalization	14
1.5.4	When writing books	15
1.5.5	Other useful stuff	15
2	The documentation driver	16
3	The implementation of the style	16
4	The implementation of cpdparse.sty	62

1 Creating diagrams

1.1 An introductory example

Let us first take a look at a simple example which should only show what you have to type into your L^AT_EX-code to get nice looking diagrams.



1) Thomas Brand:

1.Ta3 Kc2!, 2.Tf3 e×f3, 3.e3 f4, 4.e2 f5, 5.e1T f6, 6.Th1! (Te7?) f7, 7.Th7 f8D#

2) Thomas Brand:

1.Ka8 Sg1, 2.h3 Ka5, 3.h2 Kb6, 4.h×g1L+ Kc7, 5.La7 Lc6#

To use the package you have to make it available to L^AT_EX using \usepackage{diagram} inside the preamble of your document.

Then you may use the `diagram` environment to create the diagrams. For the above example I had to type the following:

```
\begin{diagram}
\author{Brand, Thomas}
\source{Problemkiste} \year{1992}
\dedic{Elmar Bartel gew.}
\pieces[2+3]{wKd1, wBe2, sKh8, sBe4, sTa4}
\stip{h\#7}
\sol{1.Ta3 Kc2!, 2.Tf3 e\x f3, 3.e3 f4, 4.e2 f5, 5.e1T f6,
      6.Th1! (Te7?) f7, 7.Th7 f8D\#}
\end{diagram}
%
\hfill
%
\begin{diagram}
\setboolean{legend}{true}
\author{Brand, Thomas}
\source{Problemkiste} \year{1992}
\pieces[3+2]{wKa4, wLb5, wSh3, sKb7, sBh4}
\stip{h\#5}
\sol{1.Ka8 Sg1, 2.h3 Ka5, 3.h2 Kb6, 4.h\x g1L+ Kc7, 5.La7 Lc6\#}
\end{diagram}
```

```
\putsol
```

diagram Any information which belongs to a problem should be put between `\begin{diagram}` and `\end{diagram}`. The above examples contains information for *authors*, *source*, *year of publication*, *stipulation*, *solution* and (in diagram 1) a *dedication*.

This information is shown around a chessboard except the solution, which is collected and put into the output using the `\putsol` command.

1.2 Elements of a diagram

This section describes the elements which may be used inside a `diagram` environment. For most of these elements there is no sense using them between `\begin{diagram}` and `\end{diagram}`. Some of them will not work outside of the environment (like —). In case you use these switches anywhere outside you will specify the information for all problems in your surrounding environment (which may be the complete document).

1.2.1 Collecting the problem information

The following information is typically given with a problem:

- With the `\author` tag you specify one author or a list of authors. If you specify more than one author, you must separate them with “;”. Normally an author is given as “*surname, givenname*”. You may change the way, how the name is interpreted by L^AT_EX using `\normalnames` and `\reversednames`. This `\author` command does only overwrite the default behaviour when used inside a diagram environment.
- Within the `Authors` command you should use the commands `\Dr`, `\Prof` and `\ProfDr` to specify these academic titles. So one may switch off the display of these titles — like it is generally done inside *Die Schwalbe*.
- With `\pieces` you specify the position to be displayed on the board. For each kind of piece you may specify a list of fields. Different lists of fields are separated by “,”. So the general syntax for specifying the position of a specific piece is:
`[color][piece]{rotation of piece}[list of squares];`
e.g. `wTa1h1` should be clear, `nKa4` is a neutral king on a4
`w s n` may be used to specify the color of the piece.
`K D T L S B C E X` may be used to specify the piece. A `C` is used for an imitator, `E` for an equihopper and `X` for a rotated equihopper. You may *not* use an optional rotation with `C`, `E` and `X`.
`R U L` may be used to specify an optional rotation: right, upside-down, left. So you may use `sDUC7` for a grashopper on c7 — displayed as an upsidedown queen.
The characters used to specify color, piece and rotation may be changed using the `\DefinePieces` command.
You may also optionally specify the number of pieces in your diagram, which then will be used to control your input automatically.

There is also support for an imitator, which is typically displayed as a black filled circle. So `\scf4` will produce the symbol of an imitator. This is shown in diagram 3.

- As an alternative notation it is possible to enter the position in *Forsyth-Edwards-Notation*. This is possible for 8×8 boards only.
As an example: The position in diagram 2 was created via
`\fen{8/1k6/8/1B6/K6p/7N/8/8}`.
As with the `\pieces` command, you may provide the number of white and black pieces as an optional parameter.
- is used to specify the stipulation of the problem, e.g. `\stipulation{\#2}` may be used to specify a *mate in two*. There is also an abbreviation `\stip` for this macro.
- may be used to specify the city and country, where the author or the authors live. I use this inside the original section of ***Die Schwalbe***. You should separate multiple cities (for multiple authors) with “;”. There is also a boolean switch `showcity`, which controls, whether this information is displayed.
- May be used to suppress the default diagram numbering (which uses a counter) and instead directly providing a diagram “number” which may be an arbitrary text. This may also be used to suppress displaying a diagram number by providing an empty argument {}.
- May be used to specify the number which was used for the problem inside an originals section.
- May be used to specify the book or magazine where the problem was issued first.
- May be used to specify e.g. the issue of a magazine where the problem was issued.
- May be used to specify the page (or pages) where the problem was issued.
- May be used to specify the different parts of the date of publication of the problem. (E.g. for problems issued in the german magazine ***Die Schwalbe*** you will typically only specify the `\month` and the `\year`. For problems issued in ***feenschach*** you may specify a period of months like `\months{7-10}`.)
- May be used to specify an award and a tournament for the problem.
- May be used to specify a dedication which was given by the author of the problem.
- May be used to specify the fairy conditions of a problem. Different conditions should be separated with “;”.
- May be used to specify the different twins of a problem. Different twins should be separated with “;”.

- May be used to specify remarks to the problem. I typically use this to explain fairy pieces on the board. You may also use the abbreviation `\rem`.
- May be used to explain rotated pieces. An example:
`\piececdefs{{ws}{TL}{Turm-L\"aufer-J\"ager}; {wn}{SU}{Nachtreiter}}`
will create
 = Turm-L\"aufer-J\"ager
 = Nachtreiter
under the diagram.
- `\solution` may be used to specify the solution of the problem. Normally this information is not used while displaying the board but it is only collected and may be put into your text using `\putsol`. There is also an abbreviation `\sol`.
- `\judgement` may be used to describe the judgement given for a problem, e.g. when you are working on an award or when you are selecting problems for a “best of ...” book.
- `\comment` may be used to specify some comment on the problem (e.g. the authors original comment.)
- `\themes` may be used to specify themes displayed in the problem. Different themes should be separated with “,”. When creating a theme index, the themes will automatically be used to create the register.
- `\genre` may be used to specify genre of the problem. Different genres should be separated with “,”. The values are intended to using L^AT_EXimport within the PDB.

When providing an empty argument to commands `\award`, `\after`, `\dedic`, `\correction` and `\version` only a warning is issued to the logfile. In previous versions of `diagram.sty` using empty arguments with the mentioned commands produced empty lines above the diagram.

There are some commands which not only collect information but normally direct result in a change of the diagram. These are:

- does not display the outer vertical lines to symbolize a verticalcylindric board.
- does not display the outer horizontal lines to symbolize a horizontalcylindric board.
- does completely suppress the outer frame e.g. to symbolize a torus board.
- sometimes you need to suppress the inner frame instead of the outer frame which is achieved by using `\noinnerframe`. You may not use this together with `\noframe`.
- displays lines to separates fieldsections for gridchess.

1.2.2 Modifying the layout of the diagram (and the solution)

There are a couple of switches which control the layout of the diagrams. These are typically used more generally, so you may specify these switches outside the `diagram` environment or use them in your own style, which depends on `cpd.sty`.

There are some switches which control the layout of the information which is displayed above a diagram:

- | | |
|--------------------------|--|
| <code>\diagleft</code> | • displays the information left aligned |
| <code>\diagcenter</code> | • displays the information centered |
| <code>\diagright</code> | • displays the information right aligned |
| <code>\widetop</code> | • is like <code>\diagcenter</code> but the information shown above the diagram may span the whole width of the page. So L ^A T _E X will not wrap long author names. |

Using `\dianamestyle` (or `\solnamestyle`) you may specify how author names are written above the boards (or before the solutions). You may use this only if you use `\reversednames` (which is the default). Otherwise it is not possible to distinguish between firstname and surname. You must specify one of the following options as parameter to `\dianamestyle` (or `\solnamestyle`):

fullname Writes the authorname as *firstname* *surname*. This is the default.

sirname Writes the *surname* only.

short Writes an abbreviation of the *firstname* and the *surname*. The abbreviation is calculated as follows:

- The first letter of the *firstname* will be used.
`\author{Brand, Thomas}` will be displayed as **T. Brand**
- When there is a combined *firstname* separated with a hyphen, each first letter will be used. (see below)
`\author{Reich, Hans-Peter}` will be displayed as **H.-P. Reich**
- When specifying the author name, you may provide the abbreviation for the firstname using the form *surname, firstname/abbreviation*.
`\author{Brand, Thomas/Th.}` will be displayed as **Th. Brand**

noname displayes nothing

`\diagramnumbering` The same way you may specify `\pagenumbering` you may specify the format the diagrams are numbered using `\diagramnumbering` and `\pagenumbering` you may specify `arabic`, `Roman`, `roman`, `Alph` or `alph`. The default used is `arabic`. This command also switches the display for diagram numbers on.

`\setmonthstyle` You may also specify the way a month is displayed using `\setmonthstyle`.

There are some boolean switches, which control whether a specific information is displayed. These are as follows:

- | | |
|---------------------------|--|
| <code>piececounter</code> | • This is a L ^A T _E X boolean, which is used to specify whether the number of pieces is displayed below the board. So you may change its value using <code>\setboolean{piececounter}{true}</code> or <code>\setboolean{piececounter}{false}</code> . |
|---------------------------|--|

<code>showcomputer</code>	<ul style="list-style-type: none">• There is a boolean value <code>computer</code>, which controls whether the information about a computer proof is displayed or not. This value may be changed using <code>\setboolean{showcomputer}{true}</code> or <code>\setboolean{showcomputer}{false}</code>. For backwards compatibility we support the macros <code>\nocomputer</code> and <code>\showcomputer</code>.
<code>showcity</code>	<ul style="list-style-type: none">• This is a boolean switch, which controls whether the information gathered using the <code>\city</code> command is displayed. The default of this value is <code>false</code>.
<code>academictitle</code>	<ul style="list-style-type: none">• This is a boolean switch, which controls whether academic titles <code>\Dr</code>, <code>\Prof</code> or <code>\ProfDr</code> — typically used within the <code>\author</code> command — are displayed. The default is <code>true</code>.
<code>legend</code>	<ul style="list-style-type: none">• This boolean controls whether a legend is displayed. The default value of this value is <code>false</code>. When legends are displayed the distance between inner and outer frame is automatically adjusted.

`\notcomputerproofedsymbol` You may specify the text, which is used indicate, whether a problem is `\computerproofedsymbol` proofed by a computer. To specify the symbol for a problem, which is proofed, is created by `\computerproofedsymbol`. To specify the symbol for a problem, which is not computer proofed, is created by `\notcomputerproofedsymbol`. You may redefine these commands by standard L^AT_EX means (`\renewcommand`).

`\selectelchfont` You may specify which font is used for the chesspieces. There are two possible fonts:

pk for the font which was originally used in the german magazine *Problemkiste*

fs for the font which was first used (and was created for) the magazine *feenschach* ♔ ♕ ♗ ♘ ♙ ♚ ♛ ♜ ♖ ♜ ♖ ♘ ♕ ♔

\diagramx In analogy to the defaults for fontsizes of a document you may specify sizes
\diagramxi of the fonts used in a diagram. The default will be set according to the fontsize
\diagramxii specified as the \documentclass option.

1.2.3 Other commands

- This overrides the normal `\label` definition such that the diagram number is displayed when using `\ref` instead of the page number.

- This macro expects a number as a parameter. The number will be used to (re-)initialize the diagram number counter. With this command the output of diagram numbers also is switched on. It must be used outside the `diagram` environment. As an optional parameter you may specify something, which will be used as prefix before the automatically updated diagram numbers. E. g. the command `\diagram[T-]{4}` will produce the following diagram numbers for the following diagrams: **T-4**, **T-5**, **T-6**,
 \dots


1.3 Special boards

1.3.1 Changing the boardsize

diagram[] Instead of using a boardsize of 8×8 some fairy problems need smaller or larger

boards. This can be achieved by specifying the rows and columns as an optional parameter to the `\begin{diagram}` environment. You first have to specify the columns and then the rows as the following examples shows.

3



is created by

```
\begin{diagram}[17x11]
\label{bigdia}
\pieces{wKUi{11}, sKRj9, sCc5b4}
\end{diagram}
```

As you can see in the example, pieces are set using the `\pieces` macro. When using boards with more than 8 lines you have to continue with characters **i**, **j**, **k**, ... In a board with more than 9 rows you have to specify the rows in curly braces { } as shown in the example.


1.3.2 Stereo- and Space-Chess-Diagrams

`stereodiagram`
`spacediagram[]`

Other boards which are used from time to time are stereochess or spacechess boards (although there are quite few people which really have such boards!). To create these boards you just have to use either the `stereodiagram` or `spacediagram` environment instead of the normal `diagram` environment. Here is an example:

4

Gerhard W. Jensch
3104. feenschach 1980
Preis




#9

C- (5+6)

5

T. R. Dawson
6595. *Fairy Chess Review* 12/1945



#2

C- (2+8)

These diagrams have been produced by the following code:

```
\begin{stereodiagram}
\author{Jensch, Gerhard W.}
\sourcenr{3104.}
\source{feenschach}
\year{1980}
\award{Preis}
\pieces{wKf3, wTf6d5A, wLe3, wSf4A, sKe5, sTc4D, sLc4C, sSc6, sBb6c4A}
\stip{\#9}
\end{stereodiagram}
\hfill
\begin{spacediagram}
\author{Dawson, T. R.}
\sourcenr{6595}.
```

```
\source{Fairy Chess Review}
\month{12}
\year{1945}
\pieces{wKc1A, wLe1A, sKa1A, sBa2Aa1Ba2Bd3Be4Bd2Ce2D}
\stip{\#2}
\end{spacediagram}
```

The main change is within the notation of the pieces, but people knowing space- or stereo-chess problems see that the notation is just one would expect.


`\spacelayout` Sometimes one would like show the different planes of a space diagram from left to right. This may be switched using the `\spacelayout` command, which takes one parameter:

vertical for planes organized bottom up

horizontal for planes organized left to right

Is produced by

6



```
\begin{spacediagram}[4x2x3]
\spacelayout{horizontal}
\end{spacediagram}
```

C- (0+0)

1.3.3 Cylindric boards / suppressing frames

```
\horizontalcylinder
\verticalcylinder
  \noframe
\noinnerframe
```


To stylize a cylindric board one typically does not show parts of the frame. When using `\verticalcylinder` the horizontal lines of the outer frame will not be drawn. `\horizontalcylinder` suppresses the drawing of the vertical lines of the outer frame. Using `\noframe` completely supresses the outer frame. `\noinnerframe` suppresses the innerframe. In case of stereo- or space-chess-diagrams `\verticalcylinder`, `\horizontalcylinder` and `\noframe` suppresses the inner frame.

1.4 Change the coloring of the fields

`\allwhite`

The `\allwhite` boolean can be used to have all white squares. Therefore dotted lines are produced to separate the squares. For convenience we provide a command `\allwhite` which switches the value of the `\allwhite` boolean to true.

7




This was produced by:

```
\begin{diagram}
\allwhite
\pieces{wKe1, wDd1, wTa1h1, wLf1c1, wSb1g1, %
         sKe8, sDd8, sTa8h8, sLf8c8, sSb8g8}
\end{diagram}
```

C- (8+8)

\switchcolors The boolean **switchcolors** may be used to switch the coloring of white and black fields. For convenience we provide a command **switchcolors** which switches the value of the **switchcolors** boolean to true.



1.4.1 figurine Notation

figurine Instead of using the **diagram**, **stereodiagram** or **spacediagram** environment one may use the **figurine** environment. This suppresses the diagram output and produces a figurine notation inside the current text.

1.4.2 Changes within the board

\nofields You may remove single fields by using the **\nofields** or **\nosquares** command.
\nosquares Using this command does make sense for empty black fields only. This command expects a list of squares separated by “,”. You may also use this command within a stereo- or space-diagram. In this case you must specify the fields the same way you do it inside the **\pieces** command.

\fieldframe You may specify single fields, which should be surrounded by a frame. This is possible using the **\fieldframe** command. You must specify the list of fields which should have frames the same way you specify fields within the **\nofields** command.

\gridlines A more general form of lines within diagrams is possible by using the **\gridlines** command. You may specify a list of horizontal or vertical lines within the diagram. Different lines should be separated by “,”. A single line must be specified as:


[plane](v or h)(x-coordinate)(y-coordinate)(length in squares)

You must specify a plane in case of stereo- or space-chess only. For a vertical line starting at the lower left corner of “c2” ending at the upper left corner of “c8” the command to use is: **\gridlines{v217}**. Concerning the coordinates and length specifications you should pay attention to put values greater 9 in curly braces { }.

\fieldtext Sometimes you need to show text on some squares. This is done using the **\fieldtext** command. The syntax for a single text is: {Text}(x-coordinate)(y-coordinate)

Now an example how to use **\gridlines**, **\nofields** and **\fieldtext** to create some “*Letter-Board*” with text inside.

9



C- (0+0)

```
\begin{diagram}[9x7]
\noinnerframe
\nofields{a2, b2, c2, a3, b3, c3, %
b5, c5, d5, b6, c6, d6, %
e1, e2, e3, e4, e5, e6, e7, %
g1, h1, h2, h2, g3, h3, g5, h5, g6, h6, g7, h7}
\gridlines{h004, h013, h033, h143, h163, h074, %
v001, v034, v142, v312, v404, v461, %
h501, h571, h632, h642, h801, h871, %
v507, v603, v643, v803, v843, v907}
\fieldtext{{\{It ...}\}c5, {\{works\}b2}}
\end{diagram}
```

1.5 Misc

1.5.1 Chess pieces within normal text

Sometimes you may need symbols of chess pieces within your normal text, e.g. to show the *Viele-Väter-Stellung* ♕c8, ♘b6, ♗a8, ♜a7. This is possible by {\wK}c8, {\wB}b6, {\sK}a8, {\sB}a7. Additionally you may use some of these symbols:

- \swL ☰ a white bishop on a black square
- \ssL ☱ a black bishop on a black square
- \wNr ☲ a white nightrider
- \nNr ☳ a neutral nightrider
- \sNr ☴ a black nightrider
- \wGh ☵ a white grashopper
- \nGh ☶ a neutral grashopper
- \sGh ☷ a black grashopper
- \Imi ● an imitator, you may also use the **Circle** notation:
- \wC ○ a white circle
- \nC ○ a neutral circle
- \sC ● a black circle
- \wE ☸ a white equihopper
- \sE ☹ a black equihopper
- \nE ☻ a neutral equihopper
- \wX ☻ a white rotated equihopper
- \sX ☹ a black rotated equihopper
- \nX ☻ a neutral rotated equihopper

1.5.2 Other often used symbols

The style also defines commands for other symbols, which are often used within the declaration of twins or when writing a solution:

\set	* setplay
\ra	→ a left to right arrow
\lra	↔ a double ended arrow
\00	O-O king side castling
\000	O-O-O queen side castling
\x	✗ for “takes”
\any	~ for an arbitrary move (you must not simply use a ~ within your text because TeX handles this as a protected space)

arrowskip It is possible, to define a prefix and/or a suffix to use before and after arrows
- typically a common separating space. Per default there is no such space. You may use the **arrowskip** environment have a common prefix and suffix before and after arrows:

```
\begin{arrowskip}{a\,}{\,b}
...
\end{arrowskip}
```

... will prefix arrows produced with \ra or \lra with a\, and suffix with \,b.

1.5.3 Internationalization

\DefinePieces This part is relevant for people who do not like the german notation for pieces and therefore want to change this within their sources. Using the german notation, you specify the color of a piece as **w**, **s** or **n**, the type of a piece as **K**, **D**, **T**, **L**, **S**, **B** and a possible rotation of a piece as **L**, **R** or **U**. To use another notation you may use the **\DefinePieces** command which takes 3 parameters.

1. the letters used to specify the colors of the pieces using the order white, black, neutral
2. the letters used to specify the type of a piece using the order king, queen, rook, bishop, knight, pawn. You may not use the characters **C**, **E** and **X**, because these are used for Circle, Equihopper and rotated Equihopper.
3. the letters used to specify an optional rotation using the order left-turned, right-turned, upside-down. You must use capital letters for this.

When using a **\DefinePieces** command, the commands are changed to its next usage (or to the end of the document). The command not only changes the pieces you may use within the **\pieces** command but also defines commands to be used within normal text, as the following example shows:

```
\DefinePieces{wbn}{KQRBNP}{LRU}
\wDU\bKR\bwB
creates ☈●♛
```

1.5.4 When writing books

`\develop` To simplify your writings you may use the macro `\develop`. This will create the following additional information during development:

- when you use `\label` in your diagrams the label will be shown at the left upper corner of the diagram.
- The given label will also be shown inside the solution and also in any register entry.
- when you have specified a `\judgement` this information will be put into the solution.

Most books on chessproblems contain registers for authors, sometimes also on themes and sources. As you already collect all these information very detailed within the `diagram` environment the generation of registers is very simple.

To create a registers of authors you need to put the `\makeaindex` command inside the preamble of your document. This instructs latex to write an intermediate file containing information about authors and the numbers of the diagrams.¹ After a first L^AT_EX run on your document, you need to convert the intermediate file. This may be done with the `makeindex` program, which will typically called like

```
makeindex -o <filename>.and <filename>.adx
```

The resulting register may be put into your document using the `\authorindex` command.

Like an index for authors you may also create indices for sources and/or themes. For an source register you need to put `\makesindex` into your document preamble; for a theme register the command is `\maketindex`. The conversion commands for the intermediate files are

```
makeindex -o <filename>.snd <filename>.sdx
```

for the source register and

```
makeindex -o <filename>.tnd <filename>.tdx
```

for the theme register.

The source register is inserted into the text using `\sourceindex` and the theme register using `\themeindex`.

1.5.5 Other useful stuff

`\solpar` In some environments — like `window` — the use of `\par` leads to unwanted effects. Therefore we use the command `\solpar` inside the definition of `\@dia@solution`, which is used to display a single solution when using `\putsol`. You may use `\renewcommand{\solpar}` to provide another definition of `\solpar` in such situations.

`\insidediagram` The problem information collected by some commands may be used in different places (author names will be shown above the diagram and at the beginning of solutions when output using `\putsol`). Therefore we need some special handling of e.g. footnotes, to avoid creating the footnotemarks multiple times. Such

¹Normally registers contain page numbers but with chess problems normally people refer to the diagram numbers.

commands should be used within `\insidediagram` as shown by the following example:

```
\begin{diagram}
\author{Else\insidediagram{\footnotemark}, Someone}
\end{diagram}
```

2 The documentation driver

The following code will generate the documentation. Since it is the first piece of code in the file, the documentation can be obtained by simply processing the file with L^AT_EX 2 _{ε} .

```
1 <*driver>
2 \documentclass[a4paper]{article}
3 \usepackage{doc}
4 \usepackage{diagram}
5 \EnableCrossrefs
6 \CodelineIndex
7 \RecordChanges
8 \begin{document}
9 \DocInput{diagram.dtx}
10 \end{document}
11 </driver>
```

3 The implementation of the style

Specifies the preamble of our style file.

```
12 <*style>
13 \ProvidesPackage{diagram}[2024/10/14]
```

`\DefaultDiagramSize` The `\DefaultDiagramSize` may be used in code to switch to the default diagram size. As this depends on the documents default font size we use the same option and execute `10pt` as default.

```
14 \newcommand*\DefaultDiagramSize{}
15 \DeclareOption{10pt}{\renewcommand*\DefaultDiagramSize{\diagramx}}
16 \DeclareOption{11pt}{\renewcommand*\DefaultDiagramSize{\diagramxi}}
17 \DeclareOption{12pt}{\renewcommand*\DefaultDiagramSize{\diagramxii}}
18 \ExecuteOptions{10pt}

19 \ProcessOptions
20 \AtBeginDocument{\DefaultDiagramSize}

21 \RequirePackage{ifthen}
22 \RequirePackage{calc}
23 \RequirePackage{pstricks}
```

Now we declare some constants to unify its usage within the style file.

```
24 \chardef\f@ur=4
25 \chardef@\ight=8
26 \newcount\elchfont
27
```

```

28 \chardef\@pkelch=0
29 \chardef\@fselch=1
30
31 \newcount\dia@type
32
33 \newboolean{@textproblem}
34 \setboolean{@textproblem}{false}
35 \def{textproblem}{\setboolean{@textproblem}{true}\let\@dia@stipulation=\relax}
36
37 \newboolean{@solafterdiagram}
38 \setboolean{@solafterdiagram}{false}
39 \def{solafterdiagram}{\setboolean{@solafterdiagram}{true}\ignorespaces}
40
41 \newif\if@vframe\@vframetrue
42 \newif\if@hframe\@hframetrue
43 \newif\if@leaveOuter\@leaveOutertrue
44
45 \newif\if@shortform
46
47 \newif\ifspace@vertical
48 \def{spacehorizontal}{\space@verticalfalse}
49
50 % \newif\ifdi@no
51 \newboolean{@cpd@numbering@global}
52 \newboolean{@cpd@numbering@local}
53 \newcounter{board@nr}
54 \renewcommand{\theboard@nr}{\thediag}
55 % \newif\iffigcnt
56 \newboolean{piececounter}
57 \newcount\r@w
58 \newcount\lin@
59 \newcount\pl@ne
60 \newcount\current@plane
61
62 \newcount\w@cnt
63 \newcount\b@cnt
64 \newcount\n@cnt
65 \newboolean{showcity}
66 \setboolean{showcity}{false}
67 \newboolean{showacademictitle}
68 \setboolean{showacademictitle}{true}
69 \newboolean{legend}
70 \setboolean{legend}{false}
71
72 \newcount@\blackfield
73 \newboolean{allwhite}
74 \setboolean{allwhite}{false}
75 \newcommand{\allwhite}{\setboolean{allwhite}{true}}
76 \newcounter{field@border}
77 \newcount@\whitefield
78 \newboolean{switchcolors}
79 \setboolean{switchcolors}{false}
80 \newcommand{\switchcolors}{\setboolean{switchcolors}{true}}

```

We have counters for each color to count the pieces on the board.

```

81 \newboolean{cpd@checkPieceCounts}
82 \newcounter{cpd@defWhitePieces}
83 \newcounter{cpd@defBlackPieces}
84 \newcounter{cpd@defNeutralPieces}
85
86 \newcounter{cpd@whitePieces}
87 \newcounter{cpd@blackPieces}
88 \newcounter{cpd@neutralPieces}
89
90 \newcounter{cpd@row}
91 \newcounter{cpd@line}
92
93 \newcommand{\cpd@stepcounterWhite}{\stepcounter{cpd@whitePieces}}
94 \newcommand{\cpd@stepcounterBlack}{\stepcounter{cpd@blackPieces}}
95 \newcommand{\cpd@stepcounterNeutral}{\stepcounter{cpd@neutralPieces}}
96 \global\let\cpd@stepcounterPieces\relax
97
98 \newcount\help@a
99 \newcount\help@b
100
101 \newbox\dia@box
102 \newbox\@cnt@box
103 \newdimen\@cnt@wd
104 \newbox\@stip@box
105
106 \newdimen\topdist\topdist\z@
107 \newbox\@test@box
108 \newdimen\@test@dimen
109 \newif\if@left
110
111 \newcount\brd@ff
112
113 \newdimen\dia@lineskip
114
115 \newdimen\board@width
116 \newdimen\bd@width
117 \newdimen\head@width
118 \newdimen\sq@width
119
120 \newdimen\grid@width
121 \newdimen\inner@frame
122 \newdimen\outer@frame
123 \newdimen\space@frame
124 \newdimen\v@frame@dist
125 \newdimen\h@frame@dist
126 \newdimen\space@frame@dist
127 \newdimen\v@space@dist
128 \newdimen\h@space@dist
129
130 \newbox\sq@box
131 \newbox\plane@box

```

We need a lot of token registers to register the information from within

the `diagram` environment. These token registers are defined here. Initially each token register is defined to contain `\relax`, which serves as an *end-marker* when parsing lists.

```

132 \newtoks\typis@tk\typis@tk={\relax}
133 \newtoks\label@tk\label@tk={\relax}
134 \newtoks\sol@tk\sol@tk={\relax}
135 \newtoks\number@tk\number@tk={\relax}
136 \newtoks\aut@tk\aut@tk={\relax}
137 \newtoks\city@tk\city@tk={\relax}
138 \newtoks\sourcenr@tk\sourcenr@tk={\relax}
139 \newtoks\source@tk\source@tk={\relax}
140 \newtoks\day@tk\day@tk={\relax}
141 \newcount\from@month\from@month=\z@
142 \newcount\tomonth\tomonth=\z@
143 \newtoks\year@tk\year@tk={\relax}
144 \newtoks\issue@tk\issue@tk={\relax}
145 \newtoks\pages@tk\pages@tk={\relax}
146 \newtoks\tournament@tk\tournament@tk={\relax}
147 \newtoks\award@tk\award@tk={\relax}
148 \newtoks\after@tk\after@tk={\relax}
149 \newtoks\version@tk\version@tk={\relax}
150 \newtoks\correction@tk\correction@tk={\relax}
151 \newtoks\dedic@tk\dedic@tk={\relax}
152 \newtoks\fideal@tk\fideal@tk={\relax}
153 \newtoks\theme@tk\theme@tk={\relax}
154 \newtoks\twins@tk\twins@tk={\relax}
155 \newtoks\judgement@tk\judgement@tk={\relax}
156 \newtoks\comment@tk\comment@tk={\relax}
157 \newtoks\computer@tk\computer@tk={-}
158 \newtoks\nofields@tk\nofields@tk={\relax}
159 \newtoks\fieldframe@tk\fieldframe@tk={\relax}
160 \newtoks\gridlines@tk\gridlines@tk={\relax}
161 \newtoks\pieces@tk\pieces@tk={\relax}
162 \newtoks\fen@tk\fen@tk={\relax}
163 \newtoks\fieldtext@tk\fieldtext@tk={\relax}
164 \newtoks\text@tk\text@tk={\relax}
165 \newtoks\stipulation@tk\stipulation@tk={\relax}
166 \newtoks\condition@tk\condition@tk={\relax}
167 \newtoks\remark@tk\remark@tk={\relax}
168 \newtoks\piecedefs@tk\piecedefs@tk={\relax}
169 \newtoks@\cpd@emptytest

```

To remember, which information has been specified, we define TeX-booleans for each command.

```

170 \newif\if@label\@labelfalse
171 \newif\if@number\@numberfalse
172 \newif\if@special\@specialfalse
173 \newif\ifauth@r\auth@rfalse
174 \newif\if@city\@cityfalse
175 \newif\if@sourcenr\@sourcenrfalse
176 \newif\if@source\@sourcefalse
177 \newif\if@date\@datefalse
178 \newif\if@day\@dayfalse
179 \newif\if@year\@yearfalse

```

```

180 \newif\if@issue\@issuefalse
181 \newif\if@pages\@pagesfalse
182 \newif\if@tournament\@tournamentfalse
183 \newif\if@award\@awardfalse
184 \newif\if@after\@afterfalse
185 \newif\if@version\@versionfalse
186 \newif\if@correction\@correctionfalse
187 \newif\if@dedication\@dedicationfalse
188 \newif\if@fidealbum\@fidealbumfalse
189 \newif\if@twins\@twinsfalse
190 \newif\if@theme\@themefalse
191 \newif\if@computer\@computerfalse
192 \newif\if@judgement\@judgementfalse
193 \newif\if@comment\@commentfalse
194 \newif\if@pieces\@piecesfalse
195 \newboolean{@cpd@fen}\setboolean{cpd@fen}{false}%
196 \newif\if@fieldtext\@fieldtextfalse
197 \newif\if@nofields\@nofieldsfalse
198 \newif\if@gridlines\@gridlinesfalse
199 \newif\if@fieldframe\@fieldframefalse
200 \newif\if@stdgrid\@stdgridfalse
201 \newboolean{showcomputer}\setboolean{showcomputer}{true}%
202 \newcommand*{\computerproofedsymbol}{C-}
203 \newcommand*{\notcomputerproofedsymbol}{C-}
204 % \newif\if@show@computer\@show@computertrue
205 \newif\if@stipulation\@stipulationfalse
206 \newif\if@condition\@conditionfalse
207 \newif\if@remark\@remarkfalse
208 \newif\if@piececdes\@piececdesfalse
209 \newif\if@typis\@typisfalse
210 \newif\if@widedias\@widediasfalse
211 \newif\ifx@twins\x@twinsfalse
212 \newif\ifx@cond\x@condfalse
213 \newif\ifimitator\imitatorfalse
214 \newif\ifnormal@names\normal@namesfalse
215 \newif\ifs@lu
216 \newif\if@develop\@developfalse
217 \newif\if@notfirst
218 \newif\if@first

219 \newwrite\s@lfd
220 \let\below@newline=\relax
221 % These are used by the ‘‘old’’ board creating mechanism
222 \newcount\@clines
223 \newcount\@rows
224 \newcount\@lines@max
225 \newcount\@rows@max
226 \newcount\@planes@max

```

The following counters are used when creating the diagram itself.

```

227 \newcounter{cpd@rowsmax}
228 \newcounter{cpd@linesmax}
229 \newcounter{cpd@current@row}
230 \newcounter{cpd@current@line}
231 \newcounter{cpd@maxsquare}

```

```

232 \newcounter{cpd@helper}
233 \newcounter{cpd@current@square@index}
234 \newcounter{cpd@current@square@value}

```

Some boolean TeX-switches used whithin stereo- or spacechess diagrams.

```

235 \newif\if@stereo\@stereofalse
236 \newif\if@space\@spacefalse

```

These boolean switches are used to control the output of registers.

```

237 \newif\if@aindex\@aindexfalse
238 \newif\if@sindex\@sindexfalse
239 \newif\if@tindex\@tindexfalse
240 \newif\ifds@label

```

\cpd@begendiagram@hook We define hooks to be executed in \begin{diagram} and \end{diagram}.

```

\cpd@enddiagram@hook 241 \newcommand{\cpd@begendiagram@hook}{}
242 \newcommand{\cpd@enddiagram@hook}{}

```

\diagram Defines the code executed in \begin{diagram}. In case no optional size is given,
\@diagram a normal 8×8 board is generated.

```

243 \def\diagram{%
244   \begin{group}%
245   \ifnextchar [{\@diagram}{\@diagram[\@ight x\@ight]}%
246 }
247
248 \def\@cpd@initsize#1#2{%
249   \setcounter{cpd@linesmax}{#1}%
250   \setcounter{cpd@rowsmax}{#2}%
251   \setcounter{cpd@maxsquare}{\value{cpd@rowsmax}*\value{cpd@linesmax}}%
252 }
253
254 \def\@diagram[#1x#2]{%
255   \lines@max=#1%
256   \rows@max=#2%
257   \cpd@initsize{#1}{#2}%
258   \pl@ne=\z@%
259   \current@plane=\z@%
260   \let\put@sq=\put@sq@normal%
261   \let\read@plane=\read@plane@normal%
262   \start@diagram%
263 }

264 \def\stereodiagram{%
265   \begin{group}%
266   \inner@frame=0.6pt%
267   \stereottrue%
268   \cpd@initsize{8}{8}%
269   \let\put@sq=\put@sq@stereo%
270   \let\read@plane=\read@plane@stereo%
271   \start@diagram%
272 }
273 \def\spacediagram{%
274   \begin{group}%
275   \inner@frame=0.6pt%
276   \spacetrue%

```

```

277   \@ifnextchar [{\@spacediagram}{\@spacediagram[5x5x5]}%
278 }
279
280 \def\@spacediagram[#1x#2x#3]{%
281   \lines@max=#1%
282   \rows@max=#2%
283   \planes@max=#3%
284   \cpd@initsize{#1}{#2}%
285   \let\put@sqz=\put@sqz@space%
286   \let\read@plane=\read@plane@space%
287   \@start@diagram%
288 }
289 \def\@start@diagram{%
290   \init@vars%
291   \let\author=\ds@author%
292   \let\day=\ds@day%
293   \let\month=\ds@month%
294   \let\year=\ds@year%
295   \let\label=\ds@label%
296   \cpd@begindiagram@hook%
297   \ignorespaces%
298 }
299
300 \def\showtypis#1{%
301   \typisttrue%
302   \typis@tk={#1}%
303   \ignorespaces%
304 }
305
306
307 \newboolean{@cpd@inside@diagram}
308 \setboolean{@cpd@inside@diagram}{false}
309 \newcommand{\insidediagram}[1]{%
310   \ifthenelse{\boolean{@cpd@inside@diagram}}{#1}{}
311 }
312 \def\enddiagram{%
313   \let\author=\orig@author%
314   \let\day=\orig@day%
315   \let\month=\orig@month%
316   \let\year=\orig@year%
317   \let\label=\orig@label%
318   \if@number%
319   \else%
320     \refstepcounter{board@nr} so \label and \ref work properly
321   \fi%
322 %
323 % Now \label@tk should be set, if wanted, so
324 % we can generate the index entries
325 %
326 \caindex%
327 \csindex%
328 \ctindex%
329 %
330 % Now \currentlabel will be set right, so we can use

```

```

331  % the original label
332  \if@label%
333      \expandafter\@set@label\the\label@tk;%
334  \fi%
335  %
336  % Now we know, if we have frames so we can setup our dimensions
337  %
338  \global\sq@width=\fontdimen\tw@\chessfont%
339  \if@stereo%
340      \bd@width=\@ight\sq@width%
341      \board@width=\@ight\sq@width%
342      \ifdim\h@frame@dist<\sq@width%
343          \h@frame@dist=\sq@width%
344      \fi%
345      % We do already skip with \v@space@dist
346      % So we use the additional skip \space@frame@dist here
347      \v@frame@dist=\space@frame@dist%
348      \ifdim\space@frame>\outer@frame%
349          \outer@frame=\space@frame%
350      \fi%
351      \advance\bd@width\tw@\inner@frame%
352      \advance\board@width\tw@\inner@frame%
353      \advance\board@width\tw@\h@frame@dist%
354      \advance\board@width\tw@\outer@frame%
355  \else\if@space%
356      \ifdim\h@frame@dist<1.5\sq@width%
357          \h@frame@dist=1.5\sq@width%
358      \fi%
359      % We do already skip with \v@space@dist
360      % So we use the additional skip \space@frame@dist here
361      \v@frame@dist=\space@frame@dist%
362      \ifdim\space@frame>\outer@frame%
363          \outer@frame=\space@frame%
364      \fi%
365  \ifspace@vertical%
366      \bd@width=\lines@max\sq@width%
367      \board@width\bd@width%
368      \advance\bd@width\tw@\inner@frame%
369      \advance\board@width\tw@\inner@frame%
370      \advance\board@width\tw@\h@frame@dist%
371      \advance\board@width\tw@\outer@frame%
372  \else%
373      \bd@width=\lines@max\sq@width%
374      \advance\bd@width\tw@\inner@frame%
375      \ifdim\h@space@dist<1.5\sq@width%
376          \h@space@dist=1.5\sq@width%
377      \fi%
378      %\h@space@dist=0.7\sq@width%
379      % Now we can compute the width of the complete board
380      \board@width\bd@width%
381      \advance\board@width\h@space@dist%
382      \multiply\board@width\planes@max%
383      \advance\board@width\h@space@dist%
384      \advance\board@width\tw@\outer@frame%

```

```

385      \fi%
386  \else%
387    \ifthenelse{\boolean{legend}}{\v@frame@dist=1.5em\h@frame@dist=1.5em}{}
388    \bd@width=\lines@max\sq@width%
389    \ifnum\lines@max>\@ight%
390      % Make the board wider
391      \board@width=\lines@max\sq@width%
392    \else%
393      % Make a normal width
394      \board@width=\@ight\sq@width%
395    \fi%
396    \advance\bd@width\tw@\inner@frame%
397    \advance\board@width\tw@\inner@frame%
398    \advance\board@width\tw@\h@frame@dist%
399    \advance\board@width\tw@\outer@frame%
400  \fi\fi%
401  \if@widetext%
402    \head@width=\textwidth%
403  \else%
404    \head@width=\board@width%
405  \fi%
406 %
407 % Now we should build the diagram itself
408 %
409 \ifthenelse{\boolean{@textproblem}}{%
410   % Put the stipulation into the \sq@box
411   \setbox\sq@box=\hbox{\vbox to \board@width{\hsize\board@width%
412     \stipfont%
413     \raggedright%
414     \sloppy%
415     \the\stipulation@tk%
416     \vfil%
417   }}%
418 }{%
419   \put@sq% This builds up the \sq@box
420   % Check, if the given number of pieces is reached
421   \ifthenelse{\boolean{cpd@checkPieceCounts}}{%
422     \ifthenelse{\value{cpd@defWhitePieces}=\value{cpd@whitePieces}}{%
423       {\errmessage{Wrong number of white pieces}}%
424     \ifthenelse{\value{cpd@defBlackPieces}=\value{cpd@blackPieces}}{%
425       {\errmessage{Wrong number of black pieces}}%
426     \ifthenelse{\value{cpd@defNeutralPieces}=\value{cpd@neutralPieces}}{%
427       {\errmessage{Wrong number of neutral pieces}}%
428     }{}%
429   }{}%
430   %
431   \global\setbox\dia@box=\hbox{\vbox{%
432     \setboolean{@cpd@inside@diagram}{true}%
433     \parindent\z@%
434     \parskip\z@%
435     \baselineskip11p@\advance\baselineskip\dia@lineskip%
436     \hsize\head@width%
437     \centering%
438     % diagram header

```

```

439 \vskip\topdist%
440 \vbox{\hsize\board@width\hbox{%
441     \if@develop\if@label%
442         \noindent\raggedright\llap{\labelfont\the\label@tk\ }%
443     \fi\fi%
444     \vbox{%
445         \hbox{\dia@above}%
446     }%
447 }%
448 \vskip\tw@p%
449 % diagram itself
450 \vtop{\hsize\board@width%
451     \hbox to \head@width{\hss\vbox{%
452         \hsize\board@width%
453         \ifthenelse{\boolean{textproblem}}{%
454             \box\sq@box%
455         }{%
456             \outer@henbox{\box\sq@box}%
457         }%
458     }\hss}%
459 % diagram trailer
460 \hbox to \head@width{\hss\vtop{%
461     \hsize\board@width%
462     \parskip\z@%
463     \raggedright%
464     \put@count%
465     \dia@below%
466 } \hss}%
467 }%
468 \setboolean{cpd@inside@diagram}{false}%
469 }% End of \dia@box
470 \do@dia@job%
471 \cpd@enddiagram@hook%
472 \endgroup%
473 }
474
475 \def\do@put@count{%
476     \ (\arabic{cpd@whitePieces}+\arabic{cpd@blackPieces}%
477     \ifthenelse{\value{cpd@neutralPieces}>0}{+\arabic{cpd@neutralPieces}}{})%
478 }
479
480 \def\put@count{%
481     % First we build the box with the figure count
482     \ifthenelse{\boolean{showcomputer}\OR\boolean{piececounter}}{%
483         \global\setbox\cnt@box=\hbox{%
484             \stipfont%
485             \ifthenelse{\boolean{showcomputer}}{%
486                 \ \ \if@computer\computerproofedsymbol\else\notcomputerproofedsymbol\fii%
487             }{}%
488             \ifthenelse{\boolean{piececounter}}{%
489                 \do@put@count%
490             }{}%
491     }%
492     \cnt@wd=\wd\cnt@box%

```

```

493      \hangindent-\@cnt@wd%
494      \hangafter\m@ne%
495      \noindent%
496      \hbox to \z@{%
497          \hbox to \board@width{\hfil\unhbox\@cnt@box}\hskip -\board@width%
498      }%
499  }{}}%
500 }%
501
502 \let\endstereodiagram=\enddiagram
503 \let\endspacediagram=\enddiagram
504 \def\figurine{%
505     \begin{group}%
506     \init@vars%
507     \let\author=\ds@author%
508     \let\day=\ds@day%
509     \let\month=\ds@month%
510     \let\year=\ds@year%
511     \let\label=\ds@label%
512     \cpd@begindiagram@hook%
513 }%
514
515 \def\endfigurine{%
516     \let\author=\orig@author%
517     \let\day=\orig@day%
518     \let\month=\orig@month%
519     \let\year=\orig@year%
520     \let\label=\orig@label%
521     \if@number%
522     \else%
523         \refstepcounter{board@nr} so \label and \ref work properly
524     \fi%
525     %
526     % Now \label@tk should be set, if wanted, so
527     % we can generate the index entries
528     %
529     \c@index%
530     \s@index%
531     \t@index%
532     %
533     % Now \currentlabel will be set right, so we can use
534     % the original label
535     %
536     \if@label%
537         \expandafter\@set@label\the\label@tk;%
538     \fi%
539     %
540     \show@figurine%
541     \cpd@enddiagram@hook%
542     \endgroup%
543 }%
544 %
545 \gdef\selectelchfont#1{%
546     \global\elchfont\csname \#1elch\endcsname\defaultelchfont%

```

547 }

Here we define commands to change fonts used for text above and below the diagram. You may redefine to adjust the fonts to your needs.

```
\authorfont
\cityfont 548 \newcommand*{\authorfont}{\bfseries}
\sourcefont 549 \newcommand*{\cityfont}{\slshape}
\awardfont 550 \newcommand*{\sourcefont}{\bfseries\itshape}
\dedicfont 551 \newcommand*{\awardfont}{\itshape}
\stipfont 552 \newcommand*{\dedicfont}{\itshape}
\remfont 553 \newcommand*{\stipfont}{\rmfamily}
\labelfont 554 \newcommand*{\remfont}{\rmfamily}
\cpd@boardfont 555 \newcommand*{\labelfont}{\rmfamily}
556 \newcommand*{\cpd@boardfont}{\rmfamily}
\legendfont 557 \newcommand*{\legendfont}{\sffamily}
```

We have three different default sizes for diagrams. The following commands switch fontsizes used for the chessfonts to typeset the diagrams.

```
\diagramx
\diagramxi 558 \newcommand*{\diagramx}{
\diagramxii 559   \ifcase\elchfont\relax%
560     \font\chessfont=pkelch12
561     \font\ctextfont=pkelch10
562   \else%
563     \font\chessfont=fselch12
564     \font\ctextfont=fselch10
565   \fi%
566   \dia@lineskip\z@
567   \dia@type\z@
568 }
569
570 \newcommand*{\diagramxi}%
571   \ifcase\elchfont\relax%
572     \font\chessfont=pkelch14
573     \font\ctextfont=pkelch11
574   \else%
575     \font\chessfont=fselch14
576     \font\ctextfont=fselch11
577   \fi%
578   \dia@lineskip\@ne\p@
579   \dia@type\@ne
580 }
581
582 \newcommand*{\diagramxii}%
583   \ifcase\elchfont\relax%
584     \font\chessfont=pkelch16
585     \font\ctextfont=pkelch12
586   \else%
587     \font\chessfont=fselch16
588     \font\ctextfont=fselch12
589   \fi%
590   \dia@lineskip\tw@\p@
591   \dia@type\tw@
```

```

592 }

\defaultelchfont \defaultelchfont is used to define the fontsize used to typeset the diagrams
depending on the documentsize.

593 \def\defaultelchfont{%
594   \ifcase\@ptsize\relax%
595     \diagramx\or%
596     \diagramxi\or%
597     \diagramxii%
598   \fi%
599 }

600 \def\dianamestyle#1{\def\@dianame{\csname @#1\endcsname}}
601 \def\solnamestyle#1{\def\@solname{\csname @#1\endcsname}}
602 \newcommand*{\diagnum}{[2] []}{%
603   \renewcommand*{\@dianumber@prefix}{#1}%
604   \setcounter{board@nr}{#2}%
605   \addtocounter{board@nr}{\m@ne}%
}

```

Now we define a couple of abbreviations and special symbols often used when setting problem chess documents.

```

\ra Arrows and specification of space (or something different) before and after ar-
\lra rows.

\rla 606 \newcommand{\@cpd@pre@arrow}{}
arrowskip 607 \newcommand{\@cpd@post@arrow}{}
          608 \newcommand{\ra}{\@cpd@pre@arrow\mbox{$\rightarrow$}\@cpd@post@arrow}
          609 \newcommand{\lra}{\@cpd@pre@arrow\mbox{$\leftarrow$}\@cpd@post@arrow}
          610 \let\rla=\lra
          611 \newcommand*{\@cpd@prepost@arrow}[2]{%
          612   \renewcommand*{\@cpd@pre@arrow}{#1}%
          613   \renewcommand*{\@cpd@post@arrow}{#2}%
          614 }
          615 \newenvironment{arrowskip}{%
          616   \@cpd@prepost@arrow%
          617 }{%
          618 }

\x
\set 619 \newcommand{\x}{\mbox{\ifmmode\times\else$\times$\fi}}
\00 620 \def\set{\kern -.05em\raise .1ex\hbox{*}}
\000 621 \def\00{\raise .25ex\hbox{-}\kern -.1em\relax}
\any 622 \def\000{\00}
\further 623 \def\000{\00\00}
          624 \def\any{\ifmmode\sim\else$\sim$\fi}
          625 \def\further{\ifmmode\rightarrow\else$\rightarrow$\fi\ \ignorespaces}

626 \def\spacelayout#1{\csname space@#1\endcsname}
627 \def\nodiagnumbering{%
628   % \global\di@nofalse
629   \setboolean{@cpd@numbering@global}{false}%
630 }
631 \newcommand*{\@dianumber@prefix}{}
632 \def\diagnumbering#1{%

```

```

633  \setboolean{@cpd@numbering@global}{true}%
634  % \global\di@nottrue%
635  \diagram{\one}%
636  \gdef\thediag{\dianumber@prefix\csname \#1\endcsname\c@board@nr}%
637 }

\diagcenter The macros \diagcenter, \diagleft and \diagright simply define the macro
\he@dpos to the corresponding paragraph alignment.
\diagleft 638 \def\diagcenter{\def\he@dpos{\centering}}
\diagright 639 \def\diagleft{\def\he@dpos{\raggedright}}
640 \def\diagright{\def\he@dpos{\raggedleft}}


\setmonthstyle The implementation of \setmonthstyle does \diagramnumber define a command which uses the given parameter as a part of the command name.
641 \def\setmonthstyle#1{\def\write@month{\csname \#1\endcsname}%

642 \def\specialdiagram#1{%
643   \ifthenelse{\equal{}{\#1}}{%
644     % We disable displaying the diagram number
645     \setboolean{@cpd@numbering@local}{false}%
646   }{%
647     \setboolean{@cpd@numbering@local}{true}%
648     \specialtrue%
649   }
650   \number@tk=\#1\@numbertrue%
651   \def\thediag{\def\@currentlabel{\#1}%
652   \ignorespaces%
653 }

\ds@label The macros \ds@label and \ds@author are defined internally and are made
\ds@author public within \begin{diagram}. This is because the macros \label and
\author are normal LATEX-macros and I want to avoid to redefine these globally.
654 \def\ds@label{%
655   \ifstar{\ds@labelfalse\ds@ xlabel}{\ds@labeltrue\ds@ xlabel}%
656 }
657 \def\ds@author#1{%
658   \aut@tk=\#1\auth@rtrue%
659   \ignorespaces%
660 }

\ds@academictitle
\Dr 661 \def\ds@academictitle#1{\ifthenelse{\boolean{showacademictitle}}{\#1}{\ignorespaces}%
\Prof 662 \newcommand{\Dr}{\ds@academictitle{Dr.}}
\ProfDr 663 \newcommand{\Prof}{\ds@academictitle{Prof.}}
664 \newcommand{\ProfDr}{\ds@academictitle{Prof.\,},Dr.}

665 \def\@cpd@warnIfEmpty#1#2{%
666   \begingroup%
667     \@cpd@emptytest=\#1%
668     \edef\@cpd@param{\the\@cpd@emptytest}%
669   \expandafter\endgroup%
670   \ifx\@cpd@param\@empty\relax%
671     \message{^^JWARNING: empty '#2' argument.^^J}%
672   \fi

```

```

673 }
674 \def\city#1{%
675   \city@tk={#1}\@citytrue%
676   \ignorespaces%
677 }
678 \def\sourcenr#1{%
679   \sourcenr@tk={#1}\@sourcenrtrue%
680   \ignorespaces%
681 }
682 \def\source#1{%
683   \source@tk={#1}\@sourcetrue%
684   \ignorespaces%
685 }
686 \def\ds@day#1{%
687   \day@tk={#1}\@daytrue\@datetrue%
688   \ignorespaces%
689 }
690 \def\ds@month#1{%
691   \from@month=#1\@datetrue%
692   \ignorespaces%
693 }
694 \def\months#1{%
695   \@months#1;%
696   \ignorespaces%
697 }
698 \def\ds@year#1{%
699   \year@tk={#1}\@yeartrue\@datetrue%
700   \ignorespaces%
701 }
702 \def\issue#1{%
703   \issue@tk={#1}\@issuetrue%
704   \ignorespaces%
705 }
706 \def\pages#1{%
707   \pages@tk={#1}\@pagestrue%
708   \ignorespaces%
709 }
710 \def\tournament#1{%
711   \tournament@tk={#1}\@tournamenttrue%
712   \ignorespaces%
713 }
714 \def\award#1{%
715   \@cpd@warnIfEmpty{#1}{award}%
716   \award@tk={#1}\@awardtrue%
717   \ignorespaces%
718 }
719 \def\version#1{%
720   \@cpd@warnIfEmpty{#1}{version}%
721   \version@tk={#1}\@versiontrue%
722   \ignorespaces%
723 }
724 \def\after#1{%
725   \@cpd@warnIfEmpty{#1}{after}%
726   \after@tk={#1}\@aftertrue%

```

```

727     \ignorespaces%
728 }
729 \def\correction#1{%
730     \cpd@warnIfEmpty{#1}{correction}%
731     \correction@tk={#1}\@correctiontrue%
732     \ignorespaces%
733 }
734 \def\dedication#1{%
735     \cpd@warnIfEmpty{#1}{dedication}%
736     \dedic@tk={#1}\@dedicationtrue%
737     \ignorespaces%
738 }
739 \def\fidealb#1{%
740     \fidealb@tk={#1}\@fidealbtrue%
741     \ignorespaces%
742 }
743 \def\pieces{%
744     \ifnextchar[%
745     {\x@pieces}%
746     {\@pieces}%
747 }
748 \def\x@pieces[#1]{%
749     % We should parse the given piececounts
750     \setboolean{cpd@checkPieceCounts}{true}%
751     \parseWhiteAndBlackCount#1+\e@list
752     \@pieces%
753 }
754 \def\@parseWhiteAndBlackCount#1+#2+{%
755     \setcounter{cpd@defWhitePieces}{#1}%
756     \setcounter{cpd@defBlackPieces}{#2}%
757     \futurelet\n@xt\cpd@checkNeutral%
758 }
759 \let\cpd@nextproc=\relax%
760 \def\cpd@checkNeutral{%
761     \if\n@xt\relax%
762         \let\cpd@nextproc=\relax%
763     \else%
764         \let\cpd@nextproc=\@parseNeutralCount%
765     \fi%
766     \cpd@nextproc%
767 }
768 \def\@parseNeutralCount#1+{%
769     \setcounter{cpd@defNeutralPieces}{#1}%
770 }
771 \def\@pieces#1{%
772     \pieces@tk={#1}\@piecestrue%
773     \ignorespaces%
774 }
775 \newcommand{\fen}[2][]{%
776     \ifthenelse{\equal{#1}{}}{%
777         {}% Do nothing
778     }{%
779         \setboolean{cpd@checkPieceCounts}{true}%
780         \parseWhiteAndBlackCount#1+\e@list

```

```

781      }%
782      \fen@tk={#2}\setboolean{@cpd@fen}{true}%
783      \ignorespaces%
784 }
785 \def\fieldtext#1{%
786   \fieldtext@tk={#1}\@fieldtexttrue%
787   \ignorespaces%
788 }
789 \def\nofields#1{%
790   \nofields@tk={#1}\@nofieldstrue%
791   \ignorespaces%
792 }
793 \let\nosquares\nofields
794 \def\gridlines#1{%
795   \gridlines@tk={#1}\@gridlinestrue%
796   \ignorespaces%
797 }
798 \def\fieldframe#1{%
799   \fieldframe@tk={#1}\@fieldframetrue%
800   \ignorespaces%
801 }
802 \def\stipulation#1{%
803   \stipulation@tk={#1}\@stipulationtrue%
804   \ignorespaces%
805 }
806 \def\condition{%
807   \@ifstar{\x@condtrue}{\condition}{\@condition}%
808 }
809 \def\@condition#1{%
810   \condition@tk={#1}\@conditiontrue%
811   \ignorespaces%
812 }
813 \def\twins{%
814   \ifstar{\x@twinstrue}{\twins}{\@twins}%
815 }
816 \def\@twins#1{%
817   \twins@tk={#1}\@twinstrue%
818   \ignorespaces%
819 }
820 \def\remark#1{%
821   \remark@tk={#1}\@remarktrue%
822   \ignorespaces%
823 }
824 \def\piecedefs#1{%
825   \piecedefs@tk={#1}\@piecedefstrue%
826   \ignorespaces%
827 }
828 % \def\@piecedef#1{\csname#1\x@piecedef\endcsname\l@oklist}%
829 % \newcommand{\piecedef}[3][ws]{%
830 %   \def\x@piecedef{#2}%
831 %   \let\@action=\@piecedef%
832 %   \hbox{\l@oklist#1\@eolist%
833 %   \ = #3}%
834 % }

```

```

835 \def\Co#1{%
836   \ifx#1+\@computertrue\computer@tk={+}\fi%
837   \ignorespaces%
838 }
839 \long\def\solution#1{%
840   \sol@tk={#1}\global\solutrue%
841   \ignorespaces%
842 }
843 \def\themes#1{%
844   \theme@tk={#1}\@themetrue%
845   \ignorespaces%
846 }
847 \def\genre#1{%
848   \relax% Currently not used within diagram.sty
849 }
850 \long\def\comment#1{%
851   \comment@tk={#1}\@commenttrue%
852   \ignorespaces%
853 }
854 \long\def\judgement#1{%
855   \judgement@tk={#1}\@judgementtrue%
856   \ignorespaces%
857 }
858 \def\noframe{%
859   \vframefalse\hframefalse%
860   \ignorespaces%
861 }
862 \def\noinnerframe{%
863   \leaveouterfalse\vframefalse\hframefalse%
864   \ignorespaces%
865 }
866 \def\verticalcylinder{%
867   \vframefalse%
868   \ignorespaces%
869 }
870 \def\horizontalcylinder{%
871   \hframefalse%
872   \ignorespaces%
873 }
874 \def\stdgrid{%
875   \stdgridtrue%
876   \ignorespaces%
877 }

```

\gridchess Here we define some abbreviations and synonyms for other macros.

```

\magic 878 \let\gridchess=\stdgrid
\tourn 879 \let\magic=\fieldframe
\dedic 880 \let\tourn=\tournament
\stip 881 \let\dedic=\dedication
\cond 882 \let\stip=\stipulation
\rem 883 \let\cond=\condition
\sol 884 \let\rem=\remark
\long\def\sol{\solution}

```

```

886 \def\develop{%
887   \o@developtrue%
888   \ignorespaces%
889 }
890 \def\showcomputer{%
891   \setboolean{showcomputer}{true}%
892   \ignorespaces%
893 }
894 \def\nocomputer{%
895   \setboolean{showcomputer}{false}%
896   \ignorespaces%
897 }
898 \def\putsol{\immediate\closeout\solfd\input\jobname.sol\cl@arsol}
899 \def\widedias{\o@widediastrue\diagcenter}
900 \def\nowidedias{\o@widediasfalse}
901 \def\normalnames{\normal@namestrue}
902 \def\reversednames{\normal@namesfalse}
903 \def\makeaindex{%
904   \o@dia@index%
905   \newindex[thediag]{author}{adx}{and}{Autorenverzeichnis}%
906   \o@aindextrue\reversednames%
907 }
908
909 \def\makesindex{%
910   \o@dia@index%
911   \newindex[thediag]{source}{sdx}{snd}{Quellenregister}%
912   \o@sindextrue%
913 }
914
915 \def\maketindex{%
916   \o@dia@index%
917   \newindex[thediag]{theme}{tdx}{tnd}{Themenregister}%
918   \o@tindextrue%
919 }
920
921 \def\authorindex{{\let\o@idxitem\o@aidxitem\printindex[author]}}
922 \def\sourceindex{\printindex[source]}
923 \def\themeindex{\printindex[theme]}
924 \def\DefinePieces#1#2#3{%
925   \o@setPieceColor#1\o@setPieceSpec#2\o@setPieceRotation#3%
926   \loop@rotation%
927   \expandafter\xdef\csname\ds@black\ds@white\ds@bishop\endcsname{%
928     \noexpand\ch@fig{20}%
929   }%
930   \expandafter\xdef\csname\ds@black\ds@black\ds@bishop\endcsname{%
931     \noexpand\ch@fig{32}%
932   }%
933   \expandafter\xdef\csname\ds@white F\endcsname{{\chessfont\ }}%
934   \expandafter\xdef\csname\ds@black F\endcsname{{\chessfont\char144}}%
935   \expandafter\xdef\csname\ds@white Nr\endcsname{%
936     \noexpand\ch@fig{109}%
937   }%
938   \expandafter\xdef\csname\ds@neutral Nr\endcsname{%
939     \noexpand\ch@fig{115}%

```

```

940   }%
941   \expandafter\xdef\csname\ds@black Nr\endcsname{%
942     \noexpand\ch@fig{121}%
943   }%
944   \expandafter\xdef\csname\ds@white Gh\endcsname{%
945     \noexpand\ch@fig{112}%
946   }%
947   \expandafter\xdef\csname\ds@neutral Gh\endcsname{%
948     \noexpand\ch@fig{118}%
949   }%
950   \expandafter\xdef\csname\ds@black Gh\endcsname{%
951     \noexpand\ch@fig{124}%
952   }%
953   \expandafter\xdef\csname\ds@white C\endcsname{%
954     \noexpand\ch@fig{145}%
955   }%
956   \expandafter\xdef\csname\ds@neutral C\endcsname{%
957     \noexpand\ch@fig{151}%
958   }%
959   \expandafter\xdef\csname\ds@black C\endcsname{%
960     \noexpand\ch@fig{157}%
961   }%
962 }
963 \def\Imi{\ch@fig{157}}
964 \def\wE{\ch@fig{216}}
965 \def\nE{\ch@fig{222}}
966 \def\sE{\ch@fig{228}}
967 \def\wX{\ch@fig{180}}
968 \def\nX{\ch@fig{186}}
969 \def\sX{\ch@fig{192}}
970

```

\dia@above The content of the box above a diagram is controlled by the macro `\dia@above`. It just delegates the information to a couple of other macros, which then generate the displayed information above the diagram.

```

971 \newboolean{above@newline}
972 \newcommand{\above@newline}{\ifthenelse{\boolean{above@newline}}{\linebreak}{\setboolean{above@newline}{false}}%
973 \def\dia@above{%
974   \setboolean{above@newline}{false}%
975   \odia@number%
976   \odia@authors%
977   \odia@city%
978   \odia@after%
979   \odia@version%
980   \odia@source%
981   \odia@correction%
982   \odia@tournament%
983   \odia@award%
984   \odia@dedic%
985   \odia@fidealbum%
986 }

```

\dia@below As before, the macro `\dia@below` creates the displayed information below the chessboard - forwarding to a couple of other macros.

```

987 \def\dia@below{%
988   \bgroup%
989   \if@stipulation%
990     \dia@stipulation%
991   \fi%
992   \ifx@cond\else%
993     \dia@condition%
994   \fi%
995   \ifx@twins\else%
996     \dia@twins%
997   \fi%
998   \dia@piecedefs%
999   \dia@remark%
1000  \ifthenelse{\boolean{@solafterdiagram}}{%
1001    \below@newline%
1002    \the\sol@tk%
1003  }{%
1004  \noindent\hbox{}\newline\hbox{}%
1005  \egroup%
1006 }

```

\@dia@number The `\@dia@number` macro simply creates the diagram number in a single paragraph.

```

1007 \def\@dia@number{%
1008   \%ifdi@no\above@newline{\authorfont\thediag}\fi%
1009   \ifthenelse{\boolean{@cpd@numbering@local}}{%
1010     \above@newline{\authorfont\thediag}%
1011   }{%
1012 }

```

\@dia@authors This macro is used to create the list of authors specified within the `\author` macro inside the `diagram` environment. Depending on the TeX-boolean `normal@names` we either simply display the registered author or parse the list of authors by using the generic `\@parseTokenList` macro.

```

1013 \def\@dia@authors{%
1014   \ifaauthr%
1015     \ifnormal@names%
1016       \above@newline
1017       {\authorfont\the\aut@tk}%
1018     \else%
1019       \let\@action=\@dia@writename% Parse the list of authors
1020       \@parseTokenlist\aut@tk;
1021     \fi%
1022   \fi%
1023 }

1024 \def\@show@city#1;{\if@notfirst\ \slash\ \else\@notfirsttrue\fi#1}
1025
1026 \def\p@rsecity#1; {\@show@city#1;\l@oklist}
1027
1028 \def\@dia@city{%
1029   \ifthenelse{\boolean{showcity}}{%
1030     \if@city%
1031       \above@newline%

```

```

1032          \bgroup%
1033          \cityfont\@notfirstfalse%
1034          \let\@action=\p@rsecity\@parseTokenlist\city@tk;%
1035          \egroup%
1036          \fi%
1037      \}{}%
1038 }
1039
1040 \def\@dia@after{%
1041     \if@after%
1042         \bgroup%
1043         \above@newline%
1044         \dedicfont\the\after@tk%
1045         \egroup%
1046     \fi%
1047 }
1048
1049 \def\@dia@version{%
1050     \if@version%
1051         \above@newline%
1052         \bgroup%
1053         \dedicfont\the\version@tk%
1054         \egroup%
1055     \fi%
1056 }
1057
1058 \def\@dia@date{%
1059     \ifnum\from@month>\z@%
1060         \if@day%
1061             \the\day@tk.\write@month\from@month%
1062         \else%
1063             \write@month\from@month%
1064         \fi%
1065         \ifnum\to@month>\z@--\write@month\to@month\fi%
1066         \if@day.\else\fi%
1067     \fi%
1068     \if@year\the\year@tk\fi%
1069 }
1070
1071 \def\@dia@source{%
1072     \if@source%
1073         \above@newline%
1074         \bgroup%
1075         \sourcefont%
1076         \if@sourcenr\the\sourcenr@tk\ \fi
1077         \the\source@tk%
1078         \if@date\ \ \fi\@dia@date%
1079         \if@issue\ \ \the\issue@tk\fi%
1080         \if@pages ,\ \the\pages@tk\fi%
1081         \egroup%
1082     \else%
1083         \if@tournament\else\if@date%
1084             \above@newline%
1085             \bgroup%

```

```

1086      \sourcefont%
1087      \@dia@date%
1088      \egroup%
1089      \fi\fi%
1090      \fi%
1091 }
1092
1093 \def\@dia@correction{%
1094   \if@correction%
1095     \above@newline%
1096     \bgroup%
1097     \dedicfont\the\correction@tk%
1098     \egroup%
1099   \fi%
1100 }
1101
1102 \def\@dia@tournament{%
1103   \if@tournament%
1104     \above@newline%
1105     \bgroup%
1106     \awardfont%
1107     \the\tournament@tk%
1108     \if@source\else\if@date%
1109       \ \ \ \ @dia@date%
1110       \fi\fi%
1111     \egroup%
1112   \fi%
1113 }
1114
1115 \def\@dia@award{%
1116   \if@award%
1117     \above@newline%
1118     \bgroup%
1119     \awardfont\the\award@tk%
1120     \egroup%
1121   \fi%
1122 }
1123
1124 \def\@dia@dedic{%
1125   \if@dedication%
1126     \above@newline%
1127     \bgroup%
1128     \dedicfont\the\dedic@tk%
1129     \egroup%
1130   \fi%
1131 }
1132
1133 \def\@show@album#1/#2;{#1 FIDE-Album #2}
1134
1135 \def\@dia@fidealbum{%
1136   \if@fidealbum%
1137     \above@newline%
1138     {\expandafter\@show@album\the\fidealbum@tk;}%
1139   \fi%

```

```

1140 }
1141
1142 \def\@twinskip{\ \ }
1143
1144 \def\@dia@stipulation{%
1145   \if@stipulation%
1146     \bgroup%
1147     \stipfont%
1148     \the\stipulation@tk%
1149     \ifx@\twins%
1150       \let\below@newline\@twinskip%
1151       \@dia@twins%
1152     \else\ifx@\cond%
1153       \let\below@newline\@twinskip%
1154       \@dia@condition%
1155       \fi\fi%
1156     \egroup%
1157     \let\below@newline\newline%
1158   \else%
1159     \x@twinsfalse%
1160     \x@condfalse%
1161     \let\below@newline\relax%
1162   \fi%
1163 }
1164
1165 \def\x@write@twin#1; {%
1166   \hskip1em#1%
1167   \iflefttrue\let\below@newline\newline%
1168   \let\@action\write@twins%
1169   \l@oklist%
1170 }
1171
1172 \def\write@twins#1; {%
1173   \setbox\@test@box=\hbox{\#1\if@left\~\fi}%
1174   \ifdim\wd\@test@box>4\sq@width%
1175     \below@newline%
1176     \iflefttrue%
1177     #1%
1178   \else%
1179     \if@left%
1180       \below@newline%
1181     \fi%
1182     \noindent\hbox to 4\sq@width{\#1\hfil}%
1183     \if@left%
1184       \ifleftfalse%
1185     \else%
1186       \iflefttrue%
1187     \fi%
1188   \fi%
1189   \let\below@newline\newline%
1190   \l@oklist%
1191 }
1192
1193 \def\@dia@twins{%

```

```

1194 \if@twins%
1195   \bgroup%
1196   \lefttrue%
1197   \remfont%
1198   \ifx@twins%
1199     \let\@action=\x@write@twin%
1200   \else%
1201     \let\@action=\write@twins%
1202   \fi%
1203   \parseTokenlist{twins@tk}%
1204   \egroup%
1205   \let\below@newline\newline%
1206 \fi%
1207 }
1208
1209 \def\@dia@condition{%
1210   \if@condition%
1211     \bgroup%
1212     \lefttrue%
1213     \remfont%
1214     \ifx@cond%
1215       \let\@action=\x@write@twin%
1216     \else%
1217       \let\@action=\write@twins%
1218     \fi%
1219     \parseTokenlist{condition@tk}%
1220     \egroup%
1221     \let\below@newline\newline%
1222   \fi%
1223 }
1224
1225 \def\check@piecedef{%
1226   \ifx\next@piecedef\relax%
1227     \let\col@action=\relax%
1228   \else%
1229     \let\col@action=\@@piecedef%
1230   \fi%
1231   \col@action%
1232 }
1233 \def\@@piecedef#1{\csname#1\x@piecedef\endcsname\parse@piecedef}
1234
1235 \def\parse@piecedef{\futurelet\next@piecedef\check@piecedef}
1236
1237 \def\@piecedef#1#2#3{%
1238   \def\x@piecedef{#2}%
1239   \below@newline%
1240   \hbox{%
1241     \parse@piecedef#1\relax%
1242     \ = #3}%
1243 }
1244
1245 \def\write@piecedefs#1; {%
1246   \@piecedef#1%
1247   \looklist%

```

```

1248 }
1249
1250 \def\@dia@piecedefs{%
1251   \if@piecedefs%
1252     \bgroup%
1253     \lefttrue%
1254     \let\below@newline\newline%
1255     \remfont\let\@action=\write@piecedefs%
1256     \parseTokenlist\piecedefs@tk;%
1257     \egroup%
1258   \fi%
1259 }
1260
1261 \def\@dia@remark{%
1262   \if@remark%
1263     \bgroup%
1264     \lefttrue%
1265     \remfont\let\@action=\write@twins%
1266     \parseTokenlist\remark@tk;%
1267     \egroup%
1268     \let\below@newline\newline%
1269   \fi%
1270 }
1271
1272 \def\parse@params#1{%
1273   \ifcase\help@a\relax
1274     \label@tk={#1}\ifx\relax#1\else\@labeltrue\fi\or%
1275     \number@tk={#1}\ifx\relax#1\else\@numbertrue\fi\or%
1276     \aut@tk={#1}\ifx\relax#1\else\@auth@rtrue\fi\or%
1277     \city@tk={#1}\ifx\relax#1\else\@citytrue\fi\or%
1278     \sourcenr@tk={#1}\ifx\relax#1\else\@sourcenrtrue\fi\or%
1279     \source@tk={#1}\ifx\relax#1\else\@sourcetrue\fi\or%
1280     \day@tk={#1}\ifx\relax#1\else\@daytrue\fi\or%
1281     \from@month=#1\or%
1282     \to@month=#1\or%
1283     \year@tk={#1}\ifx\relax#1\else\@yeartrue\fi\or%
1284     \issue@tk={#1}\ifx\relax#1\else\@issuetrue\fi\or%
1285     \pages@tk={#1}\ifx\relax#1\else\@pagestrue\fi\or%
1286     \tournament@tk={#1}\ifx\relax#1\else\@tournamenttrue\fi\or%
1287     \award@tk={#1}\ifx\relax#1\else\@awardtrue\fi\or%
1288     \after@tk={#1}\ifx\relax#1\else\@aftertrue\fi\or%
1289     \version@tk={#1}\ifx\relax#1\else\@versiontrue\fi\or%
1290     \correction@tk={#1}\ifx\relax#1\else\@correctiontrue\fi\or%
1291     \dedic@tk={#1}\ifx\relax#1\else\@dedicationtrue\fi\or%
1292     \theme@tk={#1}\ifx\relax#1\else\@themetrue\fi\or%
1293     \twins@tk={#1}\ifx\relax#1\else\@twinstrue\fi\or%
1294     \computer@tk={#1}\or%
1295     \comment@tk={#1}\ifx\relax#1\else\@commenttrue\fi\or%
1296     \judgement@tk={#1}\ifx\relax#1\else\@judgementtrue\fi\or%
1297     \sol@tk={#1}%
1298   \fi%
1299   \advance\help@a \one%
1300   \loop@klist%
1301 }

```

```

1302
1303 \def\split@param#1{%
1304   \clabelfalse\@numberfalse\auth0rfalse\@cityfalse%
1305   \@sourcenrfalse\@sourcefalse\@dayfalse\@yearfalse%
1306   \@issuefalse\@pagesfalse\@tournamentfalse\@awardfalse%
1307   \@afterfalse\@versionfalse\@correctionfalse\@dedicationfalse%
1308   \@themefalse\@twinsfalse\@commentfalse\@judgementfalse%
1309   \help@a=\z@%
1310   \let\@action=\parse@params\l@@klist#1\@elist%
1311 }
1312 \newcommand{\solpar}{\par}
1313 \def\@dia@solution{%
1314   \bgroup%
1315   \parindent\z@%
1316   \parskip\tw@p@%
1317   {\bfseries%
1318     \noindent\if@label\showlabel{\the\label@tk}\fi%
1319     \if@number\the\number@tk) \fi%
1320     \ifaauth@r%
1321       \ifnormal@names%
1322         \the\aut@tk%
1323       \else%
1324         {\notfirstfalse% We are the first one
1325           \def\name@sep{, }%
1326           \let\@action=\@sol@writename%
1327           \parseTokenlist\aut@tk;}:%
1328         \fi%
1329         \newline%
1330       \fi%
1331   }%
1332   \if@develop\if@judgement\the\judgement@tk\solpar\fi\fi%
1333   \the\sol@tk\solpar%
1334   \if@comment\the\comment@tk\solpar\fi%
1335   \egroup%
1336 }
1337 \grid@width=0.6\p@
1338 \inner@frame=0.6\p@
1339 \outer@frame=1.2\p@
1340 \space@frame=\outer@frame
1341 \v@frame@dist=\tw@p@%
1342 \h@frame@dist=\tw@p@%
1343 \space@frame@dist=\z@%
1344 \v@space@dist=1em
1345 \def\@show@figurine{%
1346   \noindent%
1347   \figurine@number%
1348   \figurine@author%
1349   \figurine@city%
1350   \figurine@after%
1351   \figurine@correction%
1352   \figurine@version%
1353   \figurine@source%
1354   \figurine@tournament%
1355   \figurine@award%

```

```

1356   \Ofigurine@dedic%
1357   \Ofigurine@pieces%
1358   \Ofigurine@stip%
1359   \Ofigurine@twins%
1360   \Ofigurine@conditions%
1361   \Ofigurine@remarks%
1362   \Ofigurine@computer%
1363 }
1364 \def\Ofigurine@number{{\authorfont\thediag}}
1365
1366 \def\p@rseauthor@figurine#1,#2; {%
1367   \if@notfirst, \else\Onotfirsttrue\fi#2 #1%
1368   \l@oklist%
1369 }
1370
1371 \def\Ofigurine@author{%
1372   {\ifauth@r%
1373     \authorfont\Onotfirstfalse%
1374     \let\@action=\p@rseauthor@figurine%
1375     \parseTokenlist\aut@tk;%
1376     \ \ %
1377   \fi}%
1378 }
1379
1380 \def\Ofigurine@city{%
1381   {\if@city%
1382     \cityfont\Onotfirstfalse%
1383     \let\@action=\p@rsecity\@parseTokenlist\city@tk;%
1384     \ \ \ %
1385   \fi}%
1386 }
1387
1388 \def\Ofigurine@after{\if@after{\dedicfont\ \ \the\after@tk}\fi}
1389
1390 \def\Ofigurine@correction{%
1391   \if@correction{\dedicfont\ \ \the\correction@tk}\fi%
1392 }
1393
1394 \def\Ofigurine@version{%
1395   \if@version{\dedicfont\ \ \the\version@tk}\fi%
1396 }
1397
1398 \def\Ofigurine@source{%
1399   {\if@source%
1400     \sourcefont%
1401     \if@sourcenr\the\sourcenr@tk\ \fi%
1402     \the\source@tk%
1403     \if@date\ \ \fi\Odia@date%
1404     \if@issue , \the\issue@tk\fi%
1405     \if@pages , \the\pages@tk\fi%
1406   \fi}%
1407 }
1408
1409 \def\Ofigurine@tournament{%

```

```

1410   \if@tournament{\awardfont\ \ \the\tournament@tk}\fi%
1411 }
1412
1413 \def\@figurine@award{%
1414   \if@award{\awardfont\ \ \the\award@tk}\fi%
1415 }
1416
1417 \def\@figurine@dedic{%
1418   \if@dedication{\awardfont\ \ \the\dedic@tk}\fi%
1419 }
1420 \def\show@squares#1{%
1421   \list{\ch@fig{\the\help@a}#1, }{%
1422     \def\@figurine@pieces{%
1423       {\if@pieces%
1424         \let\@action=\p@rsepieces%
1425         \let\piece@job\show@squares%
1426         \parseTokenlist{pieces@tk},%
1427       \fi}%
1428     }%
1429     \def\@figurine@stip{%
1430       \if@stipulation{\stipfont\ \ \the\stipulation@tk}\fi%
1431     }%
1432
1433     \def\@figurine@conditions{%
1434       \if@condition{\remfont\ \ \the\condition@tk}\fi%
1435     }%
1436
1437     \def\@figurine@twins{%
1438       \if@twins{\remfont\ \ \the\twins@tk}\fi%
1439     }%
1440
1441     \def\@figurine@computer{%
1442       \ifthenelse{\boolean{showcomputer}}{%
1443         \if@computer\ \computerproofedsymbol\fi%
1444       }{}%
1445     }%
1446
1447     \def\@figurine@remarks{%
1448       \if@remark{\stipfont\ \ \the\remark@tk}\fi%
1449     }%
1450   \def\do@dia@job{\@write@sol\ifvmode\noindent\fi\unhbox\dia@box}%
1451   \def\solhead#1{%
1452     \def\@write@sol{%
1453       \ifs@lu{%
1454         \immediate\write\s@lfd{%
1455           \noexpand\solhead{%
1456             {\the\label@tk}%
1457             {\thediag}%
1458             {\the\aut@tk}%
1459             {\the\city@tk}%
1460             {\the\sourcenr@tk}%
1461             {\the\source@tk}%
1462             {\the\day@tk}%
1463             {\the\from@month}%

```

```

1464      {\the\to@month}%
1465      {\the\year@tk}%
1466      {\the\issue@tk}%
1467      {\the\pages@tk}%
1468      {\the\tournament@tk}%
1469      {\the\award@tk}%
1470      {\the\after@tk}%
1471      {\the\version@tk}%
1472      {\the\correction@tk}%
1473      {\the\dedic@tk}%
1474      {\the\theme@tk}%
1475      {\the\twins@tk}%
1476      {\the\computer@tk}%
1477      {\the\comment@tk}%
1478      {\the\judgement@tk}%
1479      {\the\sol@tk}%
1480      } %end of \solhead
1481      }%
1482  \fi
1483 }
1484 \def\@months#1-#2;{\from@month=#1\to@month=#2\@datetrue}
1485 \def\@dia@writename#1; {\above@newline{\authorfont\@dianame#1; }\l@oklist}
1486 \def\@sol@writename#1; {\sep@names\@solname#1; \l@oklist}
1487 \def\name@sep{, \ }
1488 \def\sep@names{\if@notfirst\name@sep\else\@notfirsttrue\fi}
1489 \def\@checkshort#1/#2#3;{%
1490   \@shortformtrue%
1491   \ifx#2\empty@list\relax%
1492     \@shortformfalse%
1493   \fi%
1494 }
1495 \def\short@christian#1#2-{%
1496   \if@notfirst -\else\@notfirsttrue\fi%
1497   #1.%%
1498   \l@oklist%
1499 }
1500
1501 \def\@write@christian#1/#2;{#1}
1502
1503 \def\write@christian#1;{%
1504   \@checkshort#1/\empty@list;%
1505   \if@shortform\@write@christian#1;\else#1\fi%
1506 }
1507
1508 \def\@write@short#1/#2;{#2}
1509
1510 \def\write@short#1;{%
1511   \@checkshort#1/\empty@list;%
1512   \if@shortform%
1513     \@write@short#1;%
1514   \else%
1515     {\@notfirstfalse\let\@action\short@christian\l@oklist#1-\empty@list}%
1516   \fi%
1517 }

```

```

1518 \def\@fullname#1, #2; {\write@christian#2; #1}
1519 \def\@sirname#1, #2; {#1}
1520 \def\@short#1, #2; {\write@short#2;\ #1}
1521 \def\@noname#1, #2; {}
1522 \def\@normalname#1; {#1}
1523 \def\space@vertical{\space@verticaltrue}
1524 \def\space@horizontal{\space@verticalfalse}
1525 \def\cl@arsol{\immediate\openout\s@lf=\jobname.sol\relax}
1526 \def\getc@lor#1{%
1527   \if#1\ds@white%
1528     \help@a\z@\global%
1529     \let\cpd@stepcounterPieces\cpd@stepcounterWhite%
1530   \else\if#1\ds@neutral%
1531     \help@a=6\global%
1532     \let\cpd@stepcounterPieces\cpd@stepcounterNeutral%
1533   \else\if#1\ds@black%
1534     \help@a=12\global%
1535     \let\cpd@stepcounterPieces\cpd@stepcounterBlack%
1536   \else\errmessage{invalid color!}%
1537   \fi\fi\fi%
1538   \getpi@ce%
1539 }
1540
1541 \def\get@text#1{\text@tk={#1}\read@square}
1542
1543 \def\getpi@ce#1{\if#1B\relax\else
1544   \if#1\ds@knight\advance\help@a\@ne%
1545   \else\if#1\ds@bishop\advance\help@a\tw@%
1546   \else\if#1\ds@rook\advance\help@a\thr@@%
1547   \else\if#1\ds@queen\advance\help@a\f@ur%
1548   \else\if#1\ds@king\advance\help@a 5%
1549   \else\if#1C%
1550     % An imitator should not count for any color.
1551     \let\cpd@stepcounterPieces\relax
1552     \advance\help@a 145%
1553   \else\if#1E% Equihopper
1554     \advance\help@a 216%
1555   \else\if#1X% Equihopper senkrecht
1556     \advance\help@a 180%
1557   \else%
1558     \errmessage{invalid piece!}%
1559   \fi\fi\fi\fi\fi\fi%
1560   \futurelet\r@tate\chkr@tate%
1561 }
1562
1563 \def\chkr@tate{%
1564   \if\r@tate \ds@rotation@upsidedown\advance\help@a 108\let\nextpr@c=\skipr@t\else%
1565   \if\r@tate \ds@rotation@left\advance\help@a 36\let\nextpr@c=\skipr@t\else%
1566   \if\r@tate \ds@rotation@right\advance\help@a 72\let\nextpr@c=\skipr@t\else%
1567   \let\nextpr@c\piece@job\fi\fi\fi\nextpr@c%
1568 }
1569 \def\skipr@t#1{\piece@job}
1570 \def\l@ok{\futurelet\whatsnext\parsefi@lds}
1571 \def\parsefi@lds{%

```

```

1572 \if\whatsnext\@list%
1573   \let\nexptr@c\relax%
1574 \else
1575   \let\nexptr@c\read@square%
1576 \fi%
1577 \nexptr@c%
1578 }
1579
1580 \def\set@current@square@index#1#2{%
1581   \setcounter{cpd@current@square@index}{#1+\value{cpd@linesmax}*#2}%
1582 }
1583 \def\set@current@square@value#1{%
1584   \expandafter%
1585   \xdef\csname cpd@square@\roman{cpd@current@square@index}\endcsname{#1}%
1586 }
1587 \def\get@current@square@value{%
1588   \setcounter{cpd@current@square@value}{%
1589     {\csname cpd@square@\roman{cpd@current@square@index}\endcsname}%
1590   }
1591 \def\set@piece{%
1592   \ifnum\pl@ne=\current@plane%
1593     \cpd@stepcounterPieces%
1594     \set@current@square@index\lin@\r@w%
1595     \get@current@square@value%
1596     \ifthenelse{\value{cpd@current@square@value}=\m@ne}%
1597       {\set@current@square@value{\the\help@a}}%
1598       \ifthenelse{\value{cpd@current@square@value}=144}%
1599         {\set@current@square@value{\the\help@a+18}}%
1600         {\errmessage{Trying to set a piece to an occupied square}}%
1601   \fi%
1602   \l@ok%
1603 }
1604 \def\cpd@fen@setpiece{%
1605   \ifnum\pl@ne=\current@plane%
1606     \cpd@stepcounterPieces%
1607     \set@current@square@index{\value{cpd@line}}{\value{cpd@row}}%
1608     \get@current@square@value%
1609     \ifthenelse{\value{cpd@current@square@value}=\m@ne}%
1610       {\set@current@square@value{\the\help@a}}%
1611       \ifthenelse{\value{cpd@current@square@value}=144}%
1612         {\set@current@square@value{\the\help@a+18}}%
1613         {\errmessage{Trying to set a piece to an occupied square}}%
1614   \fi%
1615 }
1616 \def\set@nofield, {%
1617   \ifnum\pl@ne=\current@plane%
1618     \set@current@square@index\lin@\r@w%
1619     \get@current@square@value%
1620     \ifthenelse{\value{cpd@current@square@value}=\m@ne}%
1621       {}% This is an empty white square, nothing to do
1622       \ifthenelse{\value{cpd@current@square@value}=144}%
1623         {\set@current@square@value{\m@ne}}%
1624         {\errmessage{Trying to set a piece to an occupied square}}%
1625   \fi%

```

```

1626     \l@oklist%
1627 }
1628 \def\set@frame, {%
1629   \ifnum\pl@ne=\current@plane%
1630     \vGrid{\the\lin@}{\the\r@w}\@ne%
1631     \hGrid{\the\lin@}{\the\r@w}\@ne%
1632     \advance\lin@\@ne%
1633     \vGrid{\the\lin@}{\the\r@w}\@ne%
1634     \advance\lin@\m@ne\advance\r@w\@ne%
1635     \hGrid{\the\lin@}{\the\r@w}\@ne%
1636   \fi%
1637   \l@oklist%
1638 }
1639 \def\@list{\relax}
1640 \def\l@oklist{\futurelet\nextlist\ch@cklst}
1641 \def\ch@cklst{%
1642   \ifx\nextlist\@list%
1643     \let\nextpr@c=\relax%
1644   \else%
1645     \let\nextpr@c=\@action%
1646   \fi%
1647   \nextpr@c%
1648 }
1649 \def\@cpd@handle@fen#1{%
1650   \ifx#1\relax%
1651     \ifthenelse{\value{cpd@line}=8}%
1652     {%
1653       \setcounter{cpd@line}{0}%
1654       \addtocounter{cpd@row}{\m@ne}%
1655     }%
1656     {%
1657       \errmessage{FEN: there is now row to end here}%
1658     }%
1659   \else\ifx#1K\relax%
1660     \let\cpd@stepcounterPieces\cpd@stepcounterWhite%
1661     \help@a=5%
1662     \cpd@fen@setpiece%
1663     \addtocounter{cpd@line}{\@ne}%
1664   \else\ifx#1Q\relax%
1665     \let\cpd@stepcounterPieces\cpd@stepcounterWhite%
1666     \help@a=4%
1667     \cpd@fen@setpiece%
1668     \addtocounter{cpd@line}{\@ne}%
1669   \else\ifx#1R\relax%
1670     \let\cpd@stepcounterPieces\cpd@stepcounterWhite%
1671     \help@a=3%
1672     \cpd@fen@setpiece%
1673     \addtocounter{cpd@line}{\@ne}%
1674   \else\ifx#1B\relax%
1675     \let\cpd@stepcounterPieces\cpd@stepcounterWhite%
1676     \help@a=2%
1677     \cpd@fen@setpiece%
1678     \addtocounter{cpd@line}{\@ne}%
1679   \else\ifx#1N\relax%

```

```

1680      \let\cpd@stepcounterPieces\cpd@stepcounterWhite%
1681      \help@a=1%
1682      \cpd@fen@setpiece%
1683      \addtocounter{cpd@line}{\@ne}%
1684 \else\ifx#1P\relax%
1685     \let\cpd@stepcounterPieces\cpd@stepcounterWhite%
1686     \help@a=0%
1687     \cpd@fen@setpiece%
1688     \addtocounter{cpd@line}{\@ne}%
1689 \else\ifx#1k\relax%
1690     \let\cpd@stepcounterPieces\cpd@stepcounterBlack%
1691     \help@a=17%
1692     \cpd@fen@setpiece%
1693     \addtocounter{cpd@line}{\@ne}%
1694 \else\ifx#1q\relax%
1695     \let\cpd@stepcounterPieces\cpd@stepcounterBlack%
1696     \help@a=16%
1697     \cpd@fen@setpiece%
1698     \addtocounter{cpd@line}{\@ne}%
1699 \else\ifx#1r\relax%
1700     \let\cpd@stepcounterPieces\cpd@stepcounterBlack%
1701     \help@a=15%
1702     \cpd@fen@setpiece%
1703     \addtocounter{cpd@line}{\@ne}%
1704 \else\ifx#1b\relax%
1705     \let\cpd@stepcounterPieces\cpd@stepcounterBlack%
1706     \help@a=14%
1707     \cpd@fen@setpiece%
1708     \addtocounter{cpd@line}{\@ne}%
1709 \else\ifx#1n\relax%
1710     \let\cpd@stepcounterPieces\cpd@stepcounterBlack%
1711     \help@a=13%
1712     \cpd@fen@setpiece%
1713     \addtocounter{cpd@line}{\@ne}%
1714 \else\ifx#1p\relax%
1715     \let\cpd@stepcounterPieces\cpd@stepcounterBlack%
1716     \help@a=12%
1717     \cpd@fen@setpiece%
1718     \addtocounter{cpd@line}{\@ne}%
1719 \else\ifx1#1\relax%
1720     \addtocounter{cpd@line}{1}%
1721 \else\ifx2#1\relax%
1722     \addtocounter{cpd@line}{2}%
1723 \else\ifx3#1\relax%
1724     \addtocounter{cpd@line}{3}%
1725 \else\ifx4#1\relax%
1726     \addtocounter{cpd@line}{4}%
1727 \else\ifx5#1\relax%
1728     \addtocounter{cpd@line}{5}%
1729 \else\ifx6#1\relax%
1730     \addtocounter{cpd@line}{6}%
1731 \else\ifx7#1\relax%
1732     \addtocounter{cpd@line}{7}%
1733 \else\ifx8#1\relax%

```



```

1788   \raise#2\sq@width\hbox to \z@{%
1789     \hskip#1\sq@width\hskip-.5\grid@width%
1790     \vrule height#3\sq@width width\grid@width\hss%
1791   }%
1792 }
1793
1794 \def\@hGrid#1#2#3{%
1795   \raise#2\sq@width\hbox to \z@{%
1796     \hskip#1\sq@width%
1797     \vrule width#3\sq@width height .5\grid@width depth%
1798     .5\grid@width\hss%
1799   }%
1800 }
1801 \def\@selGrid#1#2, {%
1802   \ifnum\pl@ne=\current@plane%
1803     \if#1h%
1804       \@hGrid#2%
1805     \else\if#1v%
1806       \@vGrid#2%
1807     \else%
1808       \errmessage{Wrong GridSelector #1}%
1809     \fi\fi%
1810   \fi%
1811   \l@oklist%
1812 }
1813 \def\@stdgrid{%
1814   \setbox\plane@box=\vbox{\hbox{%
1815     \help@a=\tw@%
1816     \loop%
1817       \ifnum\help@a<\lines@max%
1818         \vbox{\the\help@a}{\the\rows@max}%
1819         \advance\help@a\tw@%
1820       \repeat%
1821       \help@a=\tw@%
1822     \loop%
1823       \ifnum\help@a<\rows@max%
1824         \vbox{\the\help@a}{\the\lines@max}%
1825         \advance\help@a\tw@%
1826       \repeat%
1827       \box\plane@box%
1828     }%
1829   }%
1830 \def\ds xlabel#1{%
1831   \label@tk={#1}\@labeltrue%
1832 }
1833
1834 \def\@set@label#1;{\ifds@label\label{#1}\fi}
1835 \def\init@vars{%
1836   \global\s@lufalse
1837   \ifthenelse{\boolean{@cpd@numbering@global}}{%
1838     \setboolean{@cpd@numbering@local}{true}%
1839   }{%
1840     \setboolean{@cpd@numbering@local}{false}%
1841   }%

```

```

1842 \setboolean{cpd@checkPieceCounts}{false}%
1843 \setcounter{cpd@defWhitePieces}{\z@}%
1844 \setcounter{cpd@defBlackPieces}{\z@}%
1845 \setcounter{cpd@defNeutralPieces}{\z@}%
1846 \setcounter{cpd@whitePieces}{\z@}%
1847 \setcounter{cpd@blackPieces}{\z@}%
1848 \setcounter{cpd@neutralPieces}{\z@}%
1849 \lin@\z@
1850 }
1851
1852 \def\clear@board{%
1853   \ifthenelse{\boolean{allwhite}}{\and}{\boolean{switchcolors}}{%
1854     {\errmessage{'allwhite' and 'switchcolors' do not make sense used together.}}%
1855     {\@whitefield=\m@ne\@blackfield=144}%
1856   }%
1857   \ifthenelse{\boolean{allwhite}}{\@blackfield=\m@ne}{%
1858     \ifthenelse{\boolean{switchcolors}}{\@whitefield=144\@blackfield=\m@ne}{%
1859       \setcounter{cpd@current@row}{0}%
1860       \whiledo{\value{cpd@current@row}<\value{cpd@rowsmax}}{%
1861         \setcounter{cpd@current@line}{0}%
1862         \whiledo{\value{cpd@current@line}<\value{cpd@linesmax}}{%
1863           \set@current@square@index{\value{cpd@current@line}}{\value{cpd@current@row}}%
1864           \setcounter{cpd@helper}{\the\current@plane+\value{cpd@current@line}+\value{cpd@current@row}}%
1865           \ifthenelse{\isodd{\value{cpd@helper}}}{%
1866             {\set@current@square@value{\@whitefield}}%
1867             {\set@current@square@value{\@blackfield}}%
1868             \addtocounter{cpd@current@line}{\@one}%
1869           }%
1870           \addtocounter{cpd@current@row}{\@one}%
1871         }%
1872       }%
1873     \def\put@row#1{%
1874       \lin@\z@%
1875       \help@b=#1%
1876       \advance\help@b\brd@ff%
1877       \hbox{%
1878         \ifthenelse{\boolean{legend}}{%
1879           \advance@rows'1%
1880           \llap{\raise .25\sq@width\hbox{\legendfont \char\@rows\ \ }}%
1881         }{}%
1882         \if@stereo{%
1883           \ifnum\current@plane>\z@{%
1884             \ifnum\@rows=12{%
1885               \llap{\raise .5\sq@width\hbox{\cpd@boardfont c6\ }}%
1886             \fi%
1887             \fi%
1888           \fi%
1889           \hbox to \z@{\vbox to \sq@width{}}%
1890           \set@current@square@index{\lin@\{\#1\}}%
1891           \loop{%
1892             \get@current@square@value%
1893             \ifthenelse{\value{cpd@current@square@value}=\m@ne}{%
1894               {\wF}%
1895               {\char\value{cpd@current@square@value}}%

```

```

1896      % \ifnum\count\help@b=\m@ne\wF%
1897      % \else\char\count\help@b\fi%
1898      \advance\lin@\@ne%
1899      \addtocounter{cpd@current@square@index}{1}%
1900      % \advance\help@b\@ne%
1901      \ifnum\lin@<\lines@max\repeat%
1902  }%
1903 }%
1904 % \def\put@line#1{%
1905 %   \lin@\z@%
1906 %   \help@b=#1%
1907 %   \advance\help@b\brd@ff%
1908 %   \hbox{%
1909 %     \if@stereo%
1910 %       \ifnum\current@plane>\z@%
1911 %         \ifnum@\rows=12%
1912 %           \llap{\raise .5\sq@width\hbox{\cpd@boardfont c6\ }}%
1913 %         \fi%
1914 %       \fi%
1915 %     \fi%
1916 %     \hbox to \z@{\vbox to \sq@width{}}%
1917 %     \loop%
1918 %       \ifnum\count\help@b=\m@ne\wF%
1919 %       \else\char\count\help@b\fi%
1920 %       \advance\lin@\@ne\advance\help@b\@ne%
1921 %       \ifnum\lin@<\lines@max\repeat%
1922 %     }%
1923 % }%
1924 \def\@parseTokenlist#1#2{\expandafter\l@oklist\the#1#2 \e@list}%
1925 \def\@addToPlane#1{%
1926   \setbox\plane@box=\vbox{\hbox{%
1927     \@parseTokenlist#1,%
1928     \box\plane@box%
1929   }}}%
1930 }%
1931 \def\put@plane{%
1932   % We might want gridchess
1933   \if@stdgrid%
1934     @stdgrid%
1935   \fi%
1936   % Let us first set the fieldframes
1937   \if@fieldframe%
1938     \let\@action\read@square%
1939     \let\plane@job\set@frame%
1940     @addToPlane\fieldframe@tk%
1941   \fi%
1942   % Now we set text to all squares which are given using \fieldtext
1943   \if@fieldtext%
1944     \let\@action\p@rsetext%
1945     \let\plane@job\set@text%
1946     @addToPlane\fieldtext@tk%
1947   \fi%
1948   % Then we should add the gridlines
1949   \if@gridlines%

```

```

1950      \let\@action\read@plane%
1951      \let\plane@job\@selGrid%
1952      \@addToPlane\gridlines@tk%
1953 \else%
1954     \if@stereo%
1955       \stereo@center%
1956     \fi%
1957 \fi%
1958 % In an 'allwhite' diagram we display dotted lines
1959 \ifthenelse{\boolean{allwhite}}{%
1960   \setbox\plane@box=\vbox{\hbox{%
1961     \psset{unit=\sq@width,linewidth=.4pt,linestyle=dotted,dotsep=.125}%
1962     \setcounter{field@border}{1}%
1963     \whiledo{\value{field@border}<\lines@max}{%
1964       \psline(\value{field@border},0)(\value{field@border},\rows@max)%
1965       \addtocounter{field@border}{\@ne}%
1966     }%
1967     \setcounter{field@border}{1}%
1968     \whiledo{\value{field@border}<\rows@max}{%
1969       \psline(0,\value{field@border})(\lines@max,\value{field@border})%
1970       \addtocounter{field@border}{\@ne}%
1971     }%
1972     \box\plane@box%
1973   }%
1974 }%
1975 % Now we should clear the board
1976 \clear@board%
1977 % Let us now parse the list of pieces
1978 \ifthenelse{\boolean{cpd@fen}}{%
1979   \ifthenelse{\value{cpd@rowsmax}=8}{}{\errmessage{FEN is only allowed for 8x8 boards.}}%
1980   \ifthenelse{\value{cpd@linesmax}=8}{}{\errmessage{FEN is only allowed for 8x8 boards.}}%
1981   \setcounter{cpd@row}{7}%
1982   \setcounter{cpd@line}{0}%
1983   \let\@action\@cpd@parse@fen%
1984   \parseTokenlist\fen@tk\@list%
1985 }%
1986 \if@pieces%
1987   \let\@action\p@rsepieces%
1988   \let\piece@job\@ok\let\plane@job\set@piece%
1989   \parseTokenlist\pieces@tk,%
1990 \fi%
1991 % Now we clear all fields, which are given using \nofields
1992 \if@nofields%
1993   \let\@action\read@square%
1994   \let\plane@job\set@nofield%
1995   \parseTokenlist\nofields@tk,%
1996 \fi%
1997 % Now we can put the pieces to the board
1998 \global\setbox\plane@box=\hbox{%
1999   \vbox{\rlap{\box\plane@box}}%
2000   \vbox{%
2001     \chessfont%
2002     \baselineskip=\z@\lineskip=\z@%
2003     \rows=\rows@max%

```

```

2004      % \multiply@rows by \lines@max%
2005      \loop%
2006          \advance@rows \m@ne%
2007          \put@row@rows%
2008          \ifnum\@rows>\z@\repeat%
2009      }%
2010      % Put a legend if wanted
2011      \ifthenelse{\boolean{legend}}{\vbox to \z@{}{%
2012          \vbox to \z@{\vss}%
2013          \llap{\hbox{\hspace*\inner@frame}%
2014              \lin@\z@%
2015          \loop%
2016              \hbox to \sq@width{\hfill\advance\lin@`a\legendfont\char\lin@\hfill}%
2017              \advance\lin@\@ne%
2018          \ifnum\lin@<\lines@max\repeat%
2019      }}\vss}%
2020      }{}%
2021  }{}%
2022 }%
2023 }%
2024 \def\put@sq@normal{%
2025     \put@plane%
2026     \setbox\sq@box=\hbox{%
2027         \inner@henbox{\box\plane@box}%
2028     }%
2029 }
2030 \def\put@sq@stereo{%
2031     \setbox\sq@box=\hbox{\hfil\vbox{%
2032         \current@plane=5%
2033         \vskip\v@space@dist%
2034         \loop%
2035             \advance\current@plane\m@ne%
2036             \ifnum\current@plane=\z@%
2037                 \lines@max=\@ight%
2038                 \rows@max=\@ight%
2039             \else%
2040                 \lines@max=\f@ur%
2041                 \rows@max=\f@ur%
2042             \fi%
2043             % Now we should clear the board
2044             \begingroup We need this for inner loops!
2045             \clear@board%
2046             \put@plane%
2047             \endgroup%
2048             \hbox to \bd@width{%
2049                 \hfil%
2050                 \inner@henbox{\box\plane@box}%
2051                 \ifcase\current@plane\or%
2052                     \rlap{{\cpd@boardfont\ A}}\or%
2053                     \rlap{{\cpd@boardfont\ B}}\or%
2054                     \rlap{{\cpd@boardfont\ C}}\or%
2055                     \rlap{{\cpd@boardfont\ D}}%
2056                 \fi%
2057                 \hfil%

```

```

2058      }%
2059      \vskip\v@space@dist%
2060      \ifnum\z@<\current@plane\repeat%
2061  }\hfil}%
2062 }
2063
2064 \def\stereo@center{%
2065   \ifnum\current@plane=\z@%
2066     \setbox\plane@box=\vbox{\hbox{%
2067       \chGrid\tw@\f@ur\chGrid\tw@ 6\f@ur%
2068       \cvGrid\tw@\f@ur\cvGrid6\tw@\f@ur%
2069       \box\plane@box}%
2070     }%
2071   \fi%
2072 }
2073 \def\put@sqs@space@vertical{%
2074   \setbox\sq@box=\hbox{\hfil\vbox{%
2075     \current@plane=\planes@max%
2076     \vskip\v@space@dist%
2077     \loop%
2078       \advance\current@plane\m@ne%
2079       % Now we should clear the board
2080       \begingroup% We use inner loops!
2081       \clear@board%
2082       \put@plane%
2083       \hbox to \bd@width{%
2084         \inner@henbox{\box\plane@box}%
2085         \advance\current@plane'A%
2086         \rlap{{\cpd@boardfont\ \char\current@plane}}%
2087       }%
2088       \endgroup%
2089       \vskip\v@space@dist%
2090     \ifnum\z@<\current@plane\repeat%
2091   }\hfil}%
2092 }
2093
2094 \def\put@sqs@space@horizontal{%
2095   \setbox\sq@box=\hbox{%
2096     \current@plane=\z@%
2097     \hskip\h@space@dist%
2098     \loop%
2099       % Now we should clear the board
2100       \begingroup% We use inner loops!
2101       \clear@board%
2102       \put@plane%
2103       \hbox to \bd@width{%
2104         \inner@henbox{\box\plane@box}%
2105         \advance\current@plane'A%
2106         \rlap{{\cpd@boardfont\ \char\current@plane}}%
2107       }%
2108       \endgroup%
2109       \hskip\h@space@dist%
2110       \advance\current@plane\@ne%
2111     \ifnum\planes@max>\current@plane%

```

```

2112      \repeat%
2113  }%
2114 }
2115
2116 \def\put@sqsp@space{%
2117   \ifspacet@vertical%
2118     \put@sqsp@space@vertical%
2119   \else%
2120     \put@sqsp@space@horizontal%
2121   \fi%
2122 }
2123 \def\@inner@vframe{%
2124   \if@vframe%
2125     \vrule width \inner@frame%
2126   \else%
2127     \hskip\inner@frame%
2128   \fi%
2129 }
2130
2131 \def\@inner@hframe{%
2132   \if@hframe%
2133     \hrule height \inner@frame%
2134   \else%
2135     \vskip\inner@frame%
2136   \fi%
2137 }
2138 \def\inner@v@frame@rule{%
2139   \if@stereo%
2140     \v@inner@vframe%
2141   \else\if@space%
2142     \v@inner@vframe%
2143   \else\if@leaveOuter%
2144     \vrule width \inner@frame%
2145   \else%
2146     \v@inner@vframe%
2147   \fi\fi\fi%
2148 }
2149
2150 \def\inner@h@frame@rule{%
2151   \if@stereo%
2152     \v@inner@hframe%
2153   \else\if@space%
2154     \v@inner@hframe%
2155   \else\if@leaveOuter%
2156     \hrule height \inner@frame%
2157   \else%
2158     \v@inner@hframe%
2159   \fi\fi\fi%
2160 }
2161
2162 \def\inner@henbox#1{%
2163   \hbox{%
2164     \inner@v@frame@rule{%
2165       \vbox{\inner@h@frame@rule{#1}\inner@h@frame@rule}%

```

```

2166      \inner@v@frame@rule%
2167  }%
2168 }
2169 \def\@outer@vrule{\vrule width \outer@frame}
2170
2171 \def\@outer@hrule{\hrule height \outer@frame}
2172 \def\outer@v@frame@rule{%
2173   \if@stereo%
2174     \outer@vrule%
2175   \else\if@space%
2176     \outer@vrule%
2177   \else\if@leaveOuter%
2178     \if@vframe\@outer@vrule\else\hskip\outer@frame\fi%
2179   \else%
2180     \outer@vrule%
2181   \fi\fi\fi%
2182 }
2183
2184 \def\outer@h@frame@rule{%
2185   \if@stereo%
2186     \outer@hrule%
2187   \else\if@space%
2188     \outer@hrule%
2189   \else\if@leaveOuter%
2190     \if@hframe\@outer@hrule\else\vskip\outer@frame\fi%
2191   \else%
2192     \outer@hrule%
2193   \fi\fi\fi%
2194 }
2195
2196 \def\outer@henbox#1{%
2197   \outer@h@frame@rule%
2198   \hbox{%
2199     \outer@v@frame@rule%
2200     \ifspace@vertical%
2201       \hskip\h@frame@dist%
2202     \fi%
2203     \vbox{%
2204       \ifspace@vertical%
2205         \vskip\v@frame@dist%
2206       \else%
2207         \vskip\v@space@dist%
2208       \fi%
2209     #1%
2210     \ifspace@vertical%
2211       \vskip\v@frame@dist%
2212     \else%
2213       \vskip\v@space@dist%
2214     \fi%
2215   }%
2216   \ifspace@vertical%
2217     \hskip\h@frame@dist%
2218   \fi%
2219   \outer@v@frame@rule%

```

```

2220      }%
2221      \outer@h@frame@rule%
2222  }
2223 \def\ch@fig#1{%
2224   \ifvmode\noindent\fi%
2225   \hbox{\chtextfont\lower.1\fontdimen\tw@\chtextfont\hbox{\char#1}}%
2226 }
2227 \def\@dia@index{%
2228   \@ifundefined{newindex}%
2229   {\errmessage{You should add documentstyle-option 'index'}}{}%
2230 }
2231
2232 \def\showlabel#1{%
2233   \if@develop%
2234     \raisebox{\hbox{\labelfont#1}\penalty\exhyphenpenalty}%
2235   \fi%
2236 }
2237
2238 \def\@aidxitem#1, #2, #3{%
2239   \par\medskip#1, \write@christian#2; \dotfill #3%
2240 }
2241
2242 \def\@dia@index#1\@sep#2[#3]{\index[#3]{#2!showlabel{#1}}}
2243
2244 \def\parse@aindex#1; {%
2245   \expandafter\@dia@index\the\label@tk\@sep#1[author]\l@oklist%
2246 }
2247
2248 \def\@aindex{%
2249   \if@aindex%
2250     \ifnormal@names%
2251       \errmessage{Cannot create index entries with normalnames}%
2252     \else\ifaauth@r%
2253       \let\@action=\parse@aindex\@parseTokenlist\aut@tk;%
2254     \fi\fi%
2255   \fi%
2256 }
2257
2258 \def\x@sindex#1\@sep{\expandafter\@dia@index\the\label@tk\@sep#1[source]}
2259
2260 \def\@sindex{%
2261   \if@sindex\if@source%
2262     \expandafter\x@sindex\the\source@tk\@sep%
2263   \fi\fi%
2264 }
2265
2266 \def\parse@tindex#1, {%
2267   \expandafter\@dia@index\the\label@tk\@sep#1[theme]\l@oklist%
2268 }
2269
2270 \def\@tindex{%
2271   \if@tindex\if@theme%
2272     \let\@action=\parse@tindex\@parseTokenlist\theme@tk,%
2273   \fi\fi%

```

```

2274 }
2275 \def\@setPieceColor#1#2#3{%
2276   \gdef\ds@white{#1}\gdef\ds@black{#2}\gdef\ds@neutral{#3}%
2277 }
2278
2279 \def\@setPieceSpec#1#2#3#4#5#6{%
2280   \gdef\ds@king{#1}\gdef\ds@queen{#2}\gdef\ds@rook{#3}%
2281   \gdef\ds@bishop{#4}\gdef\ds@knight{#5}\gdef\ds@pawn{#6}%
2282 }
2283
2284 \def\@setPieceRotation#1#2#3{%
2285   \gdef\ds@rotation@left{#1}\gdef\ds@rotation@right{#2}\gdef\ds@rotation@upsidedown{#3}%
2286 }
2287 \def\loop@rotation{%
2288   \bgroup%
2289     \n@cnt\z@%
2290     \help@a\z@%
2291     \loop%
2292       \ifcase\n@cnt%
2293         \def\@theRotation{}%
2294         \or%
2295           \def\@theRotation{\ds@rotation@left}%
2296         \or%
2297           \def\@theRotation{\ds@rotation@right}%
2298         \or%
2299           \def\@theRotation{\ds@rotation@upsidedown}%
2300       \fi%
2301       \loop@color%
2302       \advance\n@cnt\@ne%
2303       \advance\help@a by 36\relax%
2304     \ifnum\n@cnt<\f@ur\repeat%
2305   \egroup%
2306 }
2307
2308 \def\loop@color{%
2309   \bgroup%
2310     \w@cnt\z@%
2311     \loop%
2312       \ifcase\w@cnt%
2313         \def\@theColor{\ds@white}%
2314         \or%
2315           \def\@theColor{\ds@neutral}%
2316         \or%
2317           \def\@theColor{\ds@black}%
2318         \fi%
2319         \loop@piece%
2320         \advance\w@cnt\@ne%
2321         \advance\help@a by 6%
2322       \ifnum\w@cnt<\thr@@\repeat%
2323   \egroup%
2324 }
2325
2326 \def\loop@piece{%
2327   \bgroup%

```

```

2328      \b@cnt\z@%
2329      \loop%
2330          \ifcase\b@cnt%
2331              \def\@thePiece{\ds@pawn}%
2332          \or%
2333              \def\@thePiece{\ds@knight}%
2334          \or%
2335              \def\@thePiece{\ds@bishop}%
2336          \or%
2337              \def\@thePiece{\ds@rook}%
2338          \or%
2339              \def\@thePiece{\ds@queen}%
2340          \or%
2341              \def\@thePiece{\ds@king}%
2342          \fi%
2343          \expandafter\xdef\csname%
2344          \@theColor\@thePiece\@theRotation\endcsname{%
2345              \noexpand\ch@fig{\the\help@a}%
2346          }
2347          \advance\b@cnt\@ne%
2348          \advance\help@a by \@ne%
2349          \ifnum\b@cnt<6\repeat%
2350      \egroup%
2351 }
2352 \elchfont\@fselch
2353
2354 \defaultelchfont%
2355 \diagram{\@ne}
2356 %% \figcnttrue
2357 \setboolean{piececounter}{true}
2358 \def\@dianame{\@fullname}
2359 \def\@solname{\@fullname}
2360 \space@verticaltrue
2361 \diagramnumbering{arabic}
2362 \def\write@month{\@arabic}%
2363 \diagleft
2364 \cl@arsol
2365 \let\orig@author=\author
2366 \let\orig@day=\day
2367 \let\orig@month=\month
2368 \let\orig@year=\year
2369 \let\orig@label=\label
2370 \DefinePieces{wsn}{KDTLSB}{LRU}
2371 \newdimen\normalboardwidth
2372 \def\setboardwidth{%
2373     \normalboardwidth=\@ight\fontdimen\tw@\chessfont%
2374     \advance\normalboardwidth\tw@\inner@frame%
2375     \advance\normalboardwidth\tw@\h@frame@dist%
2376     \advance\normalboardwidth\tw@\outer@frame%
2377 }
2378
2379 \setboardwidth
2380
2381 </style>

```

4 The implementation of cpdparse.sty

The following contains the style file *cpdparse.sty*, which implements generic parsing of lists.

```
2382 <*cpdparse>
2383 \ProvidesPackage{cpdparse}[2020/12/27]
2384 \def\cpd@parse@list{\futurelet\cpd@parse@lookahead\cpd@parse@check}
2385 \def\cpd@parse@check{%
2386   \ifx\cpd@parse@lookahead\relax\relax%
2387     \let\cpd@parse@next=\relax%
2388   \else%
2389     \let\cpd@parse@next=\cpd@parse@action%
2390   \fi%
2391   \cpd@parse@next%
2392 }
2393 \end{macro}
2394 \endgroup
```

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	@checkshort	\@cpd@post@arrow
\,	664	. 1489, 1504, 1511 607–609, 613
\@@pieceundef .	1229, 1233	\@cityfalse . . . 174, 1304 \@cpd@pre@arrow
\@O	621–623	\@citytrue . . . 675, 1277 606, 608, 609, 612
\@action	831, 1019,	\@cnt@box \@cpd@prepost@arrow 611, 616
	1034, 1168,	102, 483, 492, 497
	1199, 1201,	\@cnt@wd . . . 103, 492, 493 \@cpd@warnIfEmpty
	1215, 1217,	\@commentfalse 193, 1308 . . . 665, 715,
	1255, 1265,	\@commenttrue 851, 1295 720, 725, 730, 735
	1310, 1326,	\@computerfalse . . . 191 \@currentlabel
	1374, 1383,	\@computertrue . . . 836 . . . 330, 533, 651
	1424, 1515,	\@condition . . . 807, 809 \@datefalse 177
	1645, 1938,	\@conditionfalse . . . 206 \@datetrue
	1944, 1950,	\@conditiontrue . . . 810 687, 691, 699, 1484
	1983, 1987,	\@correctionfalse \@dayfalse . . . 178, 1305
	1993, 2253, 2272	186, 1307 \@daytrue . . . 687, 1280
\@addToPlane .	1925,	\@correctiontrue \@dedicationfalse 187, 1307
	1940, 1946, 1952	731, 1290 \@dedicationtrue
\@afterfalse .	184, 1307	\@cpd@emptytest 736, 1291
\@aftertrue .	726, 1288	169, 667, 668 \@developfalse 216
\@aidxitem .	921, 2238	\@cpd@handle@fen . . . \@developtrue 887
\@aindex .	326, 529, 2248	1649, 1737 \@dia@after . . . 978, 1040
\@aindexfalse .	237	248, 257, 268, 284 \@dia@authors . . . 976, <u>1013</u>
\@aindextrue .	906	\@cpd@initsize . . . \@dia@award . . . 983, 1115
\@awardfalse .	183, 1306	668, 670 \@dia@city . . . 977, 1028
\@awardtrue .	716, 1287	\@cpd@param \@dia@condition . . .
\@blackfield .	72,	\@cpd@parse@fen 993, 1154, 1209
	1855–1857, 1866	1737, 1983

```

\@dia@correction .          \@figurine@number      \ononame ..... 1521
                            ..... 1347, 1364 \normalname ..... 1522
\@dia@date .....           \@figurine@pieces     \notfirstfalse ..
                            .. 1357, 1422 .. 1033, 1324,
\@dia@date ..              ..... 1357, 1422 .. 1373, 1382, 1515
\@dia@date ..              ..... 1361, 1447 \notfirsttrue 1024,
\@dia@dedic ..             ..... 1367, 1488, 1496
\@dia@fidealalbum ..       \@figurine@source    \numberfalse 171, 1304
                            ..... 1353, 1398 \numbertrue . 650, 1275
\@dia@index .....          \@figurine@stip .. \outer@hrule ....
                            ..... 1358, 1429 .. 2171, 2186,
\@dia@index ..             ..... 1354, 1409 2188, 2190, 2192
\@dia@number ..             \figurine@tournament \outer@vrule ....
\@dia@number ..             ..... 1359, 1437 .. 2169, 2174,
\@dia@remark ..            \figurine@version   2176, 2178, 2180
\@dia@solution ..          ..... 1352, 1394 \pagesfalse . 181, 1306
\@dia@source ..             ..... 1313, 1451 \pagestrue .. 707, 1285
\@dia@source ..             ..... 980, 1071 \parseNeutralCount
\@dia@stipulation ..       \@fullname ..... . 1518, 2358, 2359 ..... 764, 768
\@dia@stipulation ..       ..... 35, 990, 1144 \parseTokenlist .
\@dia@tournament ..        \gridlinesfalse . 198 .. 1020, 1034,
\@dia@tournament ..        ..... 982, 1102 \gridlinestru .. 795
\@dia@twins .....          \hGrid ..... 1631, 1203, 1219,
\@dia@twins ..              ..... 1635, 1794, 1256, 1266,
\@dia@version ..            ..... 1804, 1824, 2067 1327, 1375,
\@dia@version ..            ..... 979, 1049 \hframefalse ....
\@dia@writename ..         \hframetrue .. 42 1383, 1426,
\@dia@writename ..         ..... 1019, 1485 \hframetrue .. 42
\@diagram .....             ..... 1924, 1927,
\@dianame 600, 1485, 2358 \ifundefined ... 2228 1984, 1989,
\@dianumber@prefix ..       \eight .. 25, 245, 340, 1995, 2253, 2272
\@dianumber@prefix ..       ..... 341, 389, 394, \parseWhiteAndBlackCount
\@dianumber@prefix ..       ..... 603, 631, 636 341, 751, 754, 780
\@empty .....               2037, 2038, 2373 \piecedef ... 828,
\@fidealalbumfalse ..      \inner@hframe 2131, 831, 1237, 1246
\@fidealalbumtrue ..       ..... 188 2152, 2154, 2158 \pieceedeffalse . 208
\@fieldframefalse ..       \inner@vframe 2123, \pieceedeftrue .. 825
\@fieldframetrue ..        ..... 199 2140, 2142, 2146 \pieces . 746, 752, 771
\@fieldtextfalse ..         \issuemfalse .. 180, 1306 \piecesfalse .. 194
\@fieldtexttrue ..          \issuetrue .. 703, 1284 \piecestrue .. 772
\@fieldtexttrue ..          \judgementfalse .. \pkelch ..... 28
\@figurine@afters ..       ..... 192, 1308 \plane@job .. 1768,
\@figurine@afters ..       ..... 1350, 1388 \judgementtrue .. 1771, 1774,
\@figurine@author ..        ..... 1348, 1371 \judgementtrue .. 855, 1296 1777, 1779, 1781
\@figurine@award ..         ..... 1355, 1413 \labelfalse .. 170, 1304 \remarkfalse .. 207
\@figurine@city ..          \labeltrue .. 1274, 1831 \remarktrue .. 821
\@figurine@computer ..     \leaveOuterfalse .. 863 \rows .. 223, 1879,
\@figurine@computer ..     ..... 1362, 1441 \leaveOutertrue .. 43 1880, 1884,
\@figurine@conditions ..   ..... 1360, 1433 \leftfalse .. 1184 1911, 2003,
\@figurine@correction ..   ..... 1351, 1390 \lefttrue .. 1167, 1176, 2004, 2006–2008
\@figurine@dedic ..         \lines ..... 222 \selGrid .. 1801, 1951
\@figurine@dedic ..         ..... 1356, 1417 \months .. 695, 1484 \sep .. 2242, 2245,
\@figurine@dedic ..         \nofieldsfalse .. 197 1212, 1253, 1264 2258, 2262, 2267
\@figurine@dedic ..         ..... 1356, 1417 \nofieldstrue .. 790 \set@label .....
\@figurine@dedic ..         ..... 1356, 1417 \nofieldstrue .. 790 ... 333, 537, 1834
\@figurine@dedic ..         ..... 1356, 1417 \setPieceColor .. ..... 925, 2275

```

```

\@setPieceRotation      \@tindextrue ..... 918      1031, 1043,
..... 925, 2284 \@tournamentfalse      ..... 1051, 1073,
\@setPieceSpec 925, 2279 ..... 182, 1306      1084, 1095,
\@short ..... 1520 \@tournamenttrue .      1104, 1117,
\@shortformfalse 1492 ..... 711, 1286      1126, 1137, 1485
\@shortformtrue . 1490 \@twins ..... 814, 816 \addtocounter .....
\@show@album 1133, 1138 \@twinsfalse . 189, 1308 ... 605, 1654,
\@show@city . 1024, 1026 \@twinskip ..... 1663, 1668,
\@show@computertrue 204 . 1142, 1150, 1153 1673, 1678,
\@show@figurine .. ..... 540, 1345 \@twinstrue . 817, 1293 1683, 1688,
\@sindex 327, 530, 2260 \@typistrue ..... 301 1693, 1698,
\@sindexfalse ..... 238 \@vGrid ..... 1630, 1703, 1708,
\@sindextrue ..... 912 1633, 1787, 1713, 1718,
\@sirname ..... 1519 1806, 1818, 2068 1720, 1722,
\@sol@writename .. ..... 1326, 1486 \@versionfalse 185, 1307 1724, 1726,
\@solname 601, 1486, 2359 \@versiontrue 721, 1289 1728, 1730,
\@sourcefalse 176, 1305 \@vframefalse ..... 1732, 1734,
\@sourcenrfalse .. ..... 175, 1305 \@vframetrue ..... 41 1867, 1869,
\@sourcenrtrue 679, 1278 \@whitefield . 77, 1899, 1965, 1970
\@sourcetrue . 683, 1279 1855, 1857, 1865 \after .....
\@spacediagram 277, 280 \@widediafalse 210, 900 148, 726, 1044,
\@spacefalse ..... 236 \@widediatrue . 899 1288, 1388, 1470
\@spacetruue ..... 276 ..... 1501, 1505 \allwhite ..... 11, 75
\@specialfalse . 172 \@write@short 1508, 1513 \and .....
\@specialtrue .. 648 \@write@sol . 1450, 1452 \any ..... 14, 619
\@start@diagram .. 262, 271, 287, 289 \@yearfalse . 179, 1305 \arabic .....
\@stdgrid .. 1813, 1934 \@yeartrue .. 699, 1283 \arrowskip .....
\@stdgridfalse .. 200 \lrcorner ..... 442, 476, 606
\@stdgridtrue .. 875 486, 625, 833, \arrowskip (environ-
\@stereofalse ..... 235 933, 1024, 1076, ment) .....
\@stereotruue ..... 267 1078–1080, 136, 14
\@stip@box ..... 104 1109, 1142, 136, 14
\@stipulationfalse 205 1242, 1376, 1375, 1458, 2253
\@stipulationtrue 803 1384, 1388, \auth@rfalse . 173, 1304
\@test@box ..... 107, 1173, 1174 1391, 1395, \auth@rtrue .. 658, 1276
\@test@dimen ..... 108 1401, 1403, \author .....
\@theColor .. 2313, 1410, 1414, 313, 507, 516, 2365
2315, 2317, 2344 1418, 1430, \authorfont .....
\@thePiece ..... 2331, 2333, 1434, 1438, ... 548, 1008,
2335, 2337, 1443, 1448, 1010, 1017,
2339, 2341, 2344 1487, 1520, 1364, 1373, 1485
\@theRotation ..... 1912, 2052– \authorindex .. 15, 921
.. 2293, 2295, 2055, 2086, 2106 \award .....
2297, 2299, 2344 ..... 5, 714 \award@tk .....
\@themefalse . 190, 1308 A 147, 716, 1119,
\@themetrue .. 844, 1292 \above@newline ... 1287, 1414, 1469
\@tindex 328, 531, 2270 ..... 972, 1008, \awardfont ... 548,
\@tindexfalse .. 239 1010, 1016, 1106, 1119,
1410, 1414, 1418

```

B	2045, 2081, 2101	\cpd@stepcounterPieces
\b@cnt ... 63, 2328, 2330, 2347, 2349	\Co 835 96, 1529, 1532, 1535,
\baselineskip 435, 2002	\CodelineIndex 6	1551, 1593,
\bd@width 116, 340, 351, 366– 368, 373, 374, 380, 388, 396, 2048, 2083, 2103	\col@action 1227, 1229, 1231	1606, 1660, 1665, 1670, 1675, 1680, 1685, 1690, 1695, 1700, 1705, 1710, 1715
\below@newline ... 220, 1001, 1150, 1153, 1157, 1161, 1167, 1175, 1180, 1189, 1205, 1221, 1239, 1254, 1268	\comment 6, 850	\cpd@stepcounterWhite
\board@width .. 115, 341, 352–354, 367, 369–371, 380–384, 391, 394, 397–399, 404, 411, 440, 450, 452, 461, 497	\comment@tk 156, 851, 1295, 1334, 1477	93, 1529, 1660, 1665, 1670, 1675, 1680, 1685
\brd@ff 111, 1876, 1907	\computer@tk .. 157, 836, 1294, 1476	\condition@tk .. 5, 878
C	\computerproofedsymbol . 8, 202, 486, 1443	\condition@tk .. 5, 806, 883
\c@board@nr 636	\cond 5, 878	\condition@tk .. 166, 810, 1219, 1434
\centering .. 437, 638	\cond@tk .. 150, 731, 1097, 1290, 1391, 1472	\current@plane .. 60, 259, 1592, 1605, 1617, 1629, 1741, 1802, 1863, 1883, 1910, 2032, 2035, 2036, 2051, 2060, 2065, 2075, 2078, 2085, 2086, 2090, 2096, 2105, 2106, 2110, 2111
\ch@cklst .. 1640, 1641	\cpd@begndiagram@hook .. 241, 296, 512	D
\ch@fig 928, 931, 936, 939, 942, 945, 948, 951, 954, 957, 960, 963–969, 1420, 2223, 2345	\cpd@boardfont .. . 548, 1885, 1912, 2052– 2055, 2086, 2106	\day 5, 292, 314, 508, 517, 2366
\check@piecedef .. . 1225, 1235	\cpd@checkNeutral .. . 757, 760	\day@tk .. 140, 687, 1061, 1280, 1462
\chessfont 338, 560, 563, 572, 575, 584, 587, 933, 934, 2001, 2373	\cpd@fen@setpiece .. . 1604, 1662, 1667, 1672, 1677, 1682, 1687, 1692, 1697, 1702, 1707, 1712, 1717	\dedic 5, 878
\chkr@tate .. 1560, 1563	\cpd@nextproc .. . 759, 762, 764, 766	\dedic@tk .. . 151, 736, 1128, 1291, 1418, 1473
\chtextfont .. . 561, 564, 573, 576, 585, 588, 2225	\cpd@parse@action 2389	\dedication .. 5, 734, 881
\city 5, 674	\cpd@parse@check .. . 2384, 2385	\dedicfont .. . 548, 1044, 1053, 1097, 1128, 1388, 1391, 1395
\city@tk .. . 137, 675, 1034, 1277, 1383, 1459	\cpd@parse@list .. 2384	\DefaultDiagramSize .. . 14, 20
\cityfont 548, 1033, 1382	\cpd@parse@lookahead .. . 2384, 2386	\defaultelchfont .. . 546, 593, 2354
\cl@arsol 898, 1525, 2364	\cpd@parse@next .. . 2387, 2389, 2391	\DefinePieces .. . 14, 924, 2370
\clear@board .. . 1852, 1976,	\cpd@stepcounterBlack .. . 94, 1535, 1690, 1695, 1700, 1705, 1710, 1715	\develop .. . 15, 886
	\cpd@stepcounterNeutral .. . 95, 1532	\di@nofalse .. . 628
		\di@nottrue .. . 634
		\dia@above .. . 445, 971
		\dia@below .. . 465, 987

\dia@box 101, 431, 469, 1450
\dia@index 2242, 2245, 2258, 2267
\dia@lineskip 113, 435, 566, 578, 590
\dia@type 31, 567, 579, 591
\diagcenter 7, 638, 899
\diagleft 7, 638, 2363
\diagramnum 8, 602, 635, 2355
\diagramnumbering 7, 632, 2361
\diagram 243
diagram (environment) 4
diagram[] (environment) 8
\diagramx 8, 15, 558, 595
\diagramxi 8, 16, 558, 596
\diagramxii 8, 17, 558, 597
\diagright 7, 638
\dianamestyle 7, 600
\do@dia@job 470, 1450
\do@put@count 475, 489
\dotfill 2239
\Dr 4, 661
\ds@academictitle 661
\ds@author 291, 507, 654
\ds@bishop 927, 930, 1545, 2281, 2335
\ds@black 927, 930, 934, 941, 950, 959, 1533, 2276, 2317
\ds@day 292, 508, 686
\ds@king 1548, 2280, 2341
\ds@knight 1544, 2281, 2333
\ds@label 295, 511, 654
\ds@labelfalse 655
\ds@labeltrue 655
\ds@month 293, 509, 690
\ds@neutral 938, 947, 956, 1530, 2276, 2315
\ds@pawn 2281, 2331
\ds@queen 1547, 2280, 2339
\ds@rook 1546, 2280, 2337
\ds@rotation@left 1565, 2285, 2295
\ds@rotation@right 1566, 2285, 2297
\ds@rotation@upsidedown 1564, 2285, 2299
\ds@white 927, 933, 935, 944, 953, 1527, 2276, 2313
\ds@ xlabel 655, 1830
\ds@year 294, 510, 698
E
\eq@list 751, 780, 832, 1310, 1420, 1491, 1504, 1511, 1515, 1572, 1639, 1642, 1738, 1739, 1924, 1984
\edef 668
\elchfont 26, 546, 559, 571, 583, 2352
\EnableCrossrefs 5
\enddiagram 312, 502, 503
\endfigurine 515
\endspacediagram 503
\endstereodiagram 502
environments:
arrowskip 14
diagram 4
diagram[] 8
figurine 12
spacediagram[] 9
stereodiagram 9
\equal 643, 776
\ExecuteOptions 18
F
\f@ur 24, 1547, 1776, 2040, 2041, 2067, 2068, 2304
\fen 5, 775
\fen@tk 162, 782, 1984
\fidealalbum 739
\fidealalbum@tk 152, 740, 1138
\fieldframe 12, 798, 879
\fieldframe@tk 159, 799, 1940
\fieldtext 12, 785, 1942
\fieldtext@tk 163, 786, 1946
\figcnttrue 2356
\figurine 504
figurine (environment) 12
\fondimen 338, 2225, 2373
\from@month 141, 691, 1059, 1061, 1063, 1281, 1463, 1484
\further 619
\futurelet 757, 1235, 1560, 1570, 1640, 1763, 2384
G
\genre 6, 847
\get@current@square@value 1587, 1595, 1608, 1619, 1892
\get@plane@stereo 1763, 1765
\get@text 1541, 1739
\getc@lor 1526, 1738
\getpi@ce 1538, 1543
\grid@width 120, 1337, 1789, 1790, 1797, 1798
\gridchess 6, 878
\gridlines 12, 794
\gridlines@tk 160, 795, 1952
H
\h@frame@dist 125, 342, 343, 353, 356, 357, 370, 387, 398, 1342, 2201, 2217, 2375
\h@space@dist 128, 375, 376, 378, 381, 383, 2097, 2109
\he@dpos 445, 638–640
\head@width 117, 402, 404, 436, 451, 460
\help@a 98, 1273, 1299, 1309, 1420, 1528, 1531, 1534, 1544–1548, 1552, 1554, 1556, 1564–1566, 1597, 1599, 1610, 1612,

1661,	1666,	\if@leaveOuter . . .	\ifnormal@names 214,
1671,	1676, 43, 2143,	1015, 1321, 2250
1681,	1686,	2155, 2177, 2189	\ifs@lu 215, 1453
1691,	1696,	\if@left 109,	\ifspace@vertical
1701,	1706,	1173, 1179, 1183 47,
1711,	1716,	\if@nofields . 197, 1992	365, 2117, 2200,
1815,	1817–	\if@notfirst	2204, 2210, 2216
1819,	1821,	... 217, 1024,	\ifx@cond 212,
1823–1825,		1367, 1488, 1496	992, 1152, 1214
2290,	2303,	\if@number	\ifx@twins 211,
2321,	2345,	171, 318, 521, 1319	995, 1149, 1198
\help@b 99,			
1875,	1876,	\if@pages 181, 1080, 1405	\ignorespaces 39,
1896,	1897,	\if@piecedefs 208, 1251	297, 303, 625,
1900,	1906,	\if@pieces	652, 659, 661,
1907,	1918–1920	.. 194, 1423, 1986	676, 680, 684,
\hfil 497,	1182,	\if@remark	688, 692, 696,
2031,		.. 207, 1262, 1448	700, 704, 708,
2049,	2057,	\if@shortform	712, 717, 722,
2061,	2074,	... 45, 1505, 1512	727, 732, 737,
\horizontalcylinder 6, 11, 870			
\hspace 2014			
I			
\if@after 184, 1041, 1388			
\if@aindex .. 237, 2249			
\if@award 183, 1116, 1414			
\if@city 174, 1030, 1381			
\if@comment .. 193, 1334			
\if@computer			
... 191, 486, 1443			
\if@condition			
... 206, 1210, 1434			
\if@correction			
... 186, 1094, 1391			
\if@date 177, 1078,			
1083, 1108, 1403			
\if@day 178, 1060, 1066			
\if@dedication			
... 187, 1125, 1418			
\if@develop			
216, 441, 1332, 2233			
\if@fidealum 188, 1136			
\if@fieldframe 199, 1937			
\if@fieldtext 196, 1943			
\if@first 218			
\if@gridlines 198, 1949			
\if@hframe 42, 2132, 2190			
\if@issue 180, 1079, 1404			
\if@judgement 192, 1332			
\if@label			
170, 332, 441, 536, 1318			
\ifauth@r 173, 1014,			
1320, 1372, 2252			
\ifdi@no 50, 1008			
\ifds@label 240, 1834			
\iffigcnt 55			
\ifimitator 213			
J			
\jobname 898, 1525			

\judgement	6, 854	M	\normal@namesfalse
\judgement@tk		\m@ne	214, 902
. 155, 855,		605, 1596, 1609,	\normal@namestrue 901
1296, 1332, 1478		1620, 1623,	\normalboardwidth
		1634, 1654,	2371, 2373–2376
L		1758, 1855–	\normalnames 901
\l@ck 1570, 1602, 1988		1857, 1893,	\nosquares 12, 793
\l@klist 828,		1896, 1918,	\notcomputerproofedsymbol 8, 203, 486
832, 1026,		2006, 2035, 2078	\nowidedias 900
1169, 1190,		\magic 878	\number@tk 135,
1247, 1300,		\makeaindex 15, 903	650, 1275, 1319
1310, 1368,		\makesindex 15, 909	\nX 13, 968
1485, 1486,		\maketindex 15, 915	
1498, 1515,		\message 671	
1626, 1637,		\month 5, 293,	O
1640, 1737–		315, 509, 518, 2367	\O0 14, 619
1739, 1753,		\months 5, 694	\O00 14, 619
1755, 1811,			\OR 482
1924, 2245, 2267			\orig@author
\label 8		 313, 516, 2365
\label@tk 133, 323,		\n@cnt 64, 2289,	\orig@day 314, 517, 2366
333, 442, 526,		2292, 2302, 2304	\orig@label
537, 1274, 1318,		\n@xt 757, 761 317, 520, 2369
1456, 1831,		\name@sep	\orig@month
2245, 2258, 2267	 1325, 1487, 1488 315, 518, 2367
\labelfont 442, <u>548</u> , 2234		\nC 13	\orig@year 316, 519, 2368
\leftarrow 609		\nE 13, 965	\outer@frame
\legend 8		\newcommand 14, 122, 348,
\legendfont		75, 80, 93–	349, 354, 362,
. 548, 1880, 2017		95, 202, 203,	363, 371, 384,
\lin@ 58, 1594, 1618,		241, 242, 309,	399, 1339, 1340,
1630–1635,		548–558, 570,	2169, 2171,
1743, 1757,		582, 602, 606–	2178, 2190, 2376
1767, 1770,		609, 611, 619,	\outer@h@frame@rule
1773, 1776,		631, 662–664, 2184, 2197, 2221
1849, 1874,		775, 829, 972, 1312	\outer@henbox 456, 2196
1890, 1898,		\newenvironment 615	\outer@v@frame@rule
1901, 1905,		\next@piecedef 2172, 2199, 2219
1920, 1921,	 1226, 1235	P
2015, 2017–2019		\nextlist 1640, 1642	\p@rseauthor 1755
\linebreak 972		\nextptr@c 1564–	\p@rseauthor@figurine
\lines@max 224,		1567, 1573, 1366, 1374
255, 281, 366,		1575, 1577,	\p@rsecity
373, 388, 389,		1643, 1645, 1647 1026, 1034, 1383
391, 1817,		\nGh 13	\p@rsepieces
1824, 1901,		\nNr 13 1424, 1738, 1987
1921, 1963,		\nocomputer 8, 894	\p@rsetext 1739, 1944
1969, 2004,		\nodiagnumbering 627	\pages 5, 706
2019, 2037, 2040		\nofields	\pages@tk
\lineskip 2002		12, 789, 793, 1991 145, 707, 1080,
\loop@color 2301, 2308		\nofields@tk	1285, 1405, 1467
\loop@piece 2319, 2326	 158, 790, 1995	\parse@aindex 2244, 2253
\loop@rotation 926, 2287		\noframe 6, 11, 858	\parse@params 1272, 1310
\lra 14, <u>606</u>		\noinnerframe 6, 11, 862	

\parse@pieceodef ..	\put@sqc@space@vertical ..	\s@ltrue	840
.. 1233, 1235, 1241 2073, 2118	\sC	13
\parse@tindex 2266, 2272	\put@sqc@stereo ..	\sE	13, 966
\parsefi@lds 1570, 1571 269, 2030	\selectelchfont	8, 545
\piece@job .. 1425,	\putsol	\sep@names ..	1486, 1488
1567, 1569, 1988		\set	14, <u>619</u>
\piececounter .. 7	R	\set@current@square@index	
\pieceodef .. 829	\r@tate 1560, 1564–1566 1580,	
\piecedefs .. 6, 824	\r@w	1594, 1607,	
\piecedefs@tk ..	1618, 1630,	1618, 1862, 1890	
... 168, 825, 1256	1631, 1633–	\set@current@square@value	
\pieces	1635, 1742,	1583,	
\pieces@tk .. 161,	1758, 1767,	1597, 1599,	
772, 1426, 1989	1770, 1773, 1776	1610, 1612,	
\plane 59, 258, 1592,	\ra	1623, 1865, 1866	
1605, 1617,	\raggedleft	\set@frame .. 1628, 1939	
1629, 1741,	\raggedright	\set@nofield 1616, 1994	
1767, 1770,	413, 442, 463, 639	\set@piece .. 1591, 1988	
1773, 1776,	\read@plane 261, 270,	\set@text .. 1740, 1945	
1779, 1786, 1802	286, 1759, 1950	\setboardwidth ...	
\plane@box 131, 1814,	\read@plane@normal 2372, 2379	
1827, 1926,	261, 1761	\setcounter .. 249–	
1928, 1960,	\read@plane@space	251, 604, 755,	
1972, 1998,	286, 1786	756, 769, 1581,	
1999, 2027,	\read@plane@stereo	1588, 1653,	
2050, 2066,	270, 1763	1843–1848,	
2069, 2084, 2104	\read@square	1858, 1860,	
\plane@char 1541, 1575,	1863, 1962,	
.. 1763, 1766,	1756, 1938, 1993	1967, 1981, 1982	
1769, 1772, 1775	\rem	6, <u>878</u> \setmonthstyle .. 7, <u>641</u>	
\plane@job	\remark	\sffamily	557
.. 1761, 1779,	6, 820, 884	\sGh	13
1784, 1786,	\remark@tk .. 167,	\sh@wauthor	1755
1939, 1945,	821, 1266, 1448	\short@christian ..	
1951, 1988, 1994	1213, 1255, 1495, 1515	
\planes@max 226, 283,	1265, 1434, 1438	\show@squares 1420, 1425	
382, 2075, 2111	\renewcommand 15–17,	\showacademictitle .. 8	
\Prof	54, 603, 612, 613	\showcity	8
4, <u>661</u>	\reversednames 902, 906	\showcomputer .. 8, 890	
\ProfDr	4, <u>661</u> \rightarrow	\showlabel .. 1318, 2232	
\psline	1964, 1969	\showtypis	300
\psset	1961	\sim	624
\put@count .. 464, 480	\rla	\skip@plane	
\put@line	606 \rlap .. 1999, 2052–	.. 1768, 1771,	
\put@plane	2055, 2086, 2106	1774, 1777, 1784	
.. 1931, 2025,	\roman	\skip@t 1564–1566, 1569	
2046, 2082, 2102	1585, 1589 \slash	\slash	1024
\put@row .. 1873, 2007	\rows@max 225, 256,	\slappy	414
\put@sqc	282, 1818, 1823,	\slshape	549
260, 269, 285, 419	1964, 1968,	\sNr	13
\put@sqc@normal ..	2003, 2038, 2041	\sol	6, <u>878</u>
..... 260, 2024	S	\sol@tk	
\put@sqc@space 285, 2116	\s@lfd	134, 840, 1002,	
\put@sqc@space@horizontal ..	219, 898, 1454, 1525	1297, 1333, 1479	
..... 2094, 2120	\s@lufalse		

\solafterdiagram . . . 39
 \solhead 1451, 1455, 1480
 \solnamestyle . . . 7, 601
 \solpar 15,
 1312, 1332–1334
 \solution . . . 6, 839, 885
 \source 5, 682
 \source@tk 139,
 683, 1077, 1279,
 1402, 1461, 2262
 \sourcefont 548,
 1075, 1086, 1400
 \sourceindex 15, 922
 \sourcenr 5, 678
 \sourcenr@tk
 138, 679, 1076,
 1278, 1401, 1460
 \space@frame
 123, 348,
 349, 362, 363, 1340
 \space@frame@dist
 126, 346,
 347, 360, 361, 1343
 \space@horizontal 1524
 \space@vertical . 1523
 \space@verticalfalse 48, 1524
 \space@verticaltrue 1523, 2360
 \spacediagram 273
 spacediagram[] (environment) 9
 \spacehorizontal . . . 48
 \spacelayout 11, 626
 \specialdiagram 5, 642
 \split@param 1303, 1451
 \sq@box 130,
 410, 411, 419,
 454, 456, 2026,
 2031, 2074, 2095
 \sq@width 118,
 338, 340–343,
 356, 357, 366,
 373, 375, 376,
 378, 388, 391,
 394, 1174, 1182,
 1742–1745,
 1788–1790,
 1795–1797,
 1880, 1885,
 1889, 1912,
 1916, 1961, 2017
 \ssL 13
 \stdgrid 874, 878
 \stepcounter 93–95
 \stereo@center
 1955, 2064
 \stereodiagram 264
 stereodiagram (environment) 9
 \stip 5, 878
 \stipfont
 412, 484, 548,
 1147, 1430, 1448
 \stipulation 5, 802, 882
 \stipulation@tk
 165, 415,
 803, 1148, 1430
 \switchcolors 12, 80
 \swL 13
 \sX 13, 969

T
 \text@tk 164, 1541, 1747
 \textproblem 35
 \theboard@nr 54
 \thediag 54,
 636, 651, 1008,
 1010, 1364, 1457
 \theme@tk 153, 844,
 1292, 1474, 2272
 \themeindex 15, 923
 \themes 6, 843
 \thr@@ 1546, 1773, 2322
 \times 619
 \to@month 142, 1065,
 1282, 1464, 1484
 \topdist 106, 439
 \tourn 878
 \tournament 5, 710, 880
 \tournament@tk
 146, 711, 1107,
 1286, 1410, 1468
 \tw@ 338, 351–
 354, 368–371,
 374, 384, 396–
 399, 448, 590,
 591, 1316, 1341,
 1342, 1545,
 1767, 1770,
 1773, 1776,
 1815, 1819,
 1821, 1825,
 2067, 2068,
 2225, 2373–2376
 \twins 5, 813

V
 \v@frame@dist 124,
 347, 361, 387,
 1341, 2205, 2211
 \v@space@dist
 127, 345,
 359, 1344, 2033,
 2059, 2076,
 2089, 2207, 2213
 \value 251, 422, 424,
 426, 477, 1581,
 1596, 1598,
 1607, 1609,
 1611, 1620,
 1622, 1651,
 1859, 1861–
 1864, 1893,
 1895, 1963,
 1964, 1968,
 1969, 1979, 1980
 \version 719
 \version@tk
 149, 721, 1053,
 1289, 1395, 1471
 \verticalcylinder 6, 11, 866

W
 \w@cnt 62, 2310,
 2312, 2320, 2322
 \wC 13
 \wE 13, 964
 \wF 1894, 1896, 1918
 \wGh 13
 \whatsnext 1570, 1572
 \whiledo 1859,
 1861, 1963, 1968
 \widedias 7, 899
 \wNr 13
 \write@christian
 1503, 1518, 2239
 \write@month
 641, 1061,
 1063, 1065, 2362
 \write@piecedefs
 1245, 1255
 \write@short 1510, 1520
 \write@twins
 1168, 1172,
 1201, 1217, 1265

\wX	13, 967	830, 1233, 1238	Y
		\x@pieces ... 745, 748	\year ... 5, 294,
X		\x@index ... 2258, 2262	316, 510, 519, 2368
\x	14, 619	\x@twinsfalse 211, 1159	\year@tk . 143, 699,
\x@condfalse	212, 1160	\x@twinstrue ... 814	1068, 1283, 1465
\x@condtrue	807	\x@write@twin ...	
\x@piecedef	828,	. 1165, 1199, 1215	

Change History

v0.1	naming collising with options from eurosym.sty.	1
General: First Version		
v0.2		
General: Added the documentation for the <i>information collecting</i> macros which may be used inside a environment.	1	
v0.3		
General: Added list of commands which should not be indexed.	1	
v0.4		
General: Added most missing user documentation.	1	
v0.5		
General: Fixed wrong piece count when using imitators	1	
v0.6		
General: Changed erroneous code to parse given piececount.	1	
v1.10		
General: Fixed issue: 03f/658:om: diagram.sty: evaluation of options 11pt and 12pt does not work.	1	
v1.11		
General: Fixed issue 03f/e20:om: diagram.sty: piecedefs should be written after twins and before remarks.	1	
v1.11.1		
General: Fixed issue 03f/b31:om: diagram.sty: label and ref don't respect diagnum prefix or diagnumbering setting.	1	
v1.12		
General: Implemented issue: 03f/fc0:om: diagram.dtx: change def x to newcommand. Changed name of internal commands ds@left, ds@right, ds@upsidedown due to a		
v1.13	General: Implemented issue: 03f/99b:om: diagram.dtx: added new command fen to allow entering forsyth-edwards-notation	1
v1.14	General: Fixed issue with stereo- and space-diagrams.	1
v1.15	General: Fixed frame issue with stereo- and space-diagrams. Added hook commands for begin/end diagram.	1
v1.16	General: Fixed date display issue in figurine environment. Added hook commands to figurine environment. Fixed documentation bug: separation character in themes command is comma not semicolon. command diagnumbering fixed: boolean is changed to true globally.	1
v1.17	General: Added generation of cpdparse.sty containing generic command for parsing lists.	1
v1.18	General: 03f/0be:om: Typo: above@newline 03f/035:om: solnamestype has no effect	1
v1.19	General: Minor fix in cl@arsol Added (empty) command gerne.	1

v1.20	General: Introduced two booleans to better control displaying diagram number globally and locally. Removed the old boolean 'di@no'.	1	versions of @writelnname command, to be able to change it in other stylefiles for the part over the diagram without influencing the one used for the solution. Added commands to set white, black and neutral Circles within text.	1
v1.21	General: Impletentd issue: 03f/309: handle empty arguments in information collecting commands Fixed typo in @dia@fidealbum command. . .	1	v1.5.5	General: Changed amount of lowering figurine pieces.
v1.22	General: Fix empty argument detection. Change ra and lra commands to allow for common prefix and suffix. Added generic command insidediagram to allow e.g. footnotes inside diagrams. Fixed numbering when creating empty diagram numbering via speciadiagram.	1	v1.5.6	General: Added new command 'solpar' to allow use of 'putsol' inside a window environment. . .
v1.5	General: Added license meta-comment to publish package on ctan.	1	v1.6	General: Added boolean showcity and code to suppress display of city, when showcity is false. Added commands for academic titles, which allow to suppress their display.
v1.5.1	General: Fixed font problem when writing producing piececounter in small diagrams.	1	v1.6.1	General: Added new command piecedefs specify names of fairy pieces for rotated pieces. . .
v1.5.2	General: Added some percent signs at line ends in @start@diagram and enddiagram to avoid accidentally added spaces.	1	v1.6.2	General: Added boolean for allwhite problems.
v1.5.3	General: Changed switch, which is used to decide, whether infomration about computer proof is displayed to use standard boolean syntax. Symbols about computer proof are now created by standard commands and may therefore be changed by users.	1	v1.6.3	General: Added boolean for board with switched field colors.
v1.5.4	General: Defined 2 different		v1.6.4	General: Added convenience command for 'allwhite' and 'switchcolors' booleans.
			v1.6.5	General: As suggested by Torsten Linß and Thomas Brand added support for Equihopper and turned Equihopper (X) . . .
			v1.6.6	General: Introduced new command to switch to the default diagram size.
			v1.6.7	General: Fixed issue '19a' with allwhite on quadratic fields.
			v1.7.0	General: Implemented Issue '32c': the command diagnum now allows to specify a prefix to

be used for the following diagrams.	1	boolean solafterdiagram to latex boolean.	1
v1.8.0		v1.9	
General: Implemented issue '03f/f2a': Added code to display a legend around the board, controlled by the boolean 'legend'.	1	General: Implemented issue '03f/932': Renamed boardfont to cpd@boardfont due to a naming collision with another chess package. Changed all font definitions to newcommand instead of def. . .	1
v1.8.1			
General: Implemented issue '03f/83c': changed tex			